



A MITEL
PRODUCT
GUIDE

OpenScape Business

Overview about released SIP Providers

Release Number 05/2025

Table of Contents

1.	Introduction	8
2.	Definition of Features	9
3.	ITSP Details	10
3.1.	International	10
3.1.1.	Broadcloud	10
3.1.2.	COLT international	11
3.1.3.	Kwebbl SIP Trunk	12
3.1.4.	Skype connect international	12
3.1.5.	Verizon international	13
3.1.6.	Virtual-Call	13
3.2.	Australia	14
3.2.1.	AAPT SIP Connect	14
3.2.2.	Broadcloud	14
3.2.3.	Commander Primus	14
3.2.4.	engin	15
3.2.5.	Internode	15
3.2.6.	Spark Voice Connect SIP	15
3.3.	Austria	16
3.3.1.	A1 SIPtrunk - registrierend	16
3.3.2.	Drei Business SIP Connect	17
3.3.3.	Magenta Business Voice SIP	18
3.3.4.	Kabelplus Business Phone	18
3.3.5.	IP-Austria	19
3.3.6.	LinzAG City Voice	19
3.3.7.	Net4You-Voice4Biz	20
3.3.8.	Neotel	20
3.3.9.	Peoplefone AG	21
3.3.10.	SalzburgAG CableLink	21
3.4.	Belgium	22
3.4.1.	Belgacom.IMS / Proximus	22
3.4.2.	BCOM	22
3.4.3.	Destiny	22
3.4.4.	BKM	23
3.4.5.	gnTel	23
3.4.6.	IPnexia – Belgium - Luxemburg	24
3.4.7.	ORANGE	25
3.4.8.	Proximus Enterprise Voice	26
3.4.9.	Telenet	27
3.4.10.	WIN	27
3.4.11.	X2COM	27
3.5.	Brazil	28
3.5.1.	vivo	28
3.5.2.	Voitel	28
3.6.	Canada	29
3.6.1.	BabyTEL	29
3.7.	Chile	29
3.7.1.	ENTEL NGN	29

3.8.	Czech Republic	30
3.8.1.	GTS	30
3.8.2.	O2 CZ	30
3.8.3.	T-mobile	30
3.9.	Denmark	31
3.9.1.	Global Connect	31
3.9.2.	TDC DK	31
3.9.3.	Telia	32
3.9.4.	Uni-tel A/S	32
3.10.	Finland	33
3.10.1.	Elisa	33
3.10.2.	Länsilinkki	33
3.10.3.	TDC	33
3.10.4.	TeliaSonera	34
3.11.	Estonia	34
3.11.1.	Telia	34
3.12.	France	35
3.12.1.	Bouygues	35
3.12.2.	Broadcloud	35
3.12.3.	codepi	35
3.12.4.	Completel	36
3.12.5.	Dstny	37
3.12.6.	Foliateam Opérateur	38
3.12.7.	Hexatel	38
3.12.8.	IP Directions	39
3.12.9.	IPnexia	39
3.12.10.	Jaguar	40
3.12.11.	Keyyo	40
3.12.12.	MyStream	40
3.12.13.	OpenIP	42
3.12.14.	Orange Business Services SIP trunking	42
3.12.15.	Paritel Operateur	43
3.12.16.	Sewan Communications	43
3.13.	Germany	44
3.13.1.	1&1	44
3.13.2.	1&1 Versatel	44
3.13.3.	autphone	45
3.13.4.	Broadcloud	45
3.13.5.	BITel	46
3.13.6.	Datel	47
3.13.7.	Deutsche Telefon	48
3.13.8.	easybell	49
3.13.9.	EasyFone	50
3.13.10.	ecotel sipTrunk 2.0	51
3.13.11.	ennit	52
3.13.12.	envia TEL	52
3.13.13.	equada	52
3.13.14.	ewe	53
3.13.15.	Gamma	54
3.13.16.	gmx	54

3.13.17.	gnTel	55
3.13.18.	GVG Glasfaser	55
3.13.19.	Helinet	56
3.13.20.	herweck callamar	57
3.13.21.	HL komm	57
3.13.22.	htp	58
3.13.23.	Inexio	59
3.13.24.	komroVoIP-Trunk	60
3.13.25.	M-Net Premium	61
3.13.26.	MK Netzdienste	62
3.13.27.	NetCologne ProPhone SIP	63
3.13.28.	NetCom BW	64
3.13.29.	NFON	65
3.13.30.	O2 All-IP Voice SIP	66
3.13.31.	omnidat	67
3.13.32.	Peoplefone AG (DE)	67
3.13.33.	PhoneVoice	68
3.13.34.	purtel	68
3.13.35.	Plusnet IPfonie Extended	69
3.13.36.	Plusnet IPfonie Extended Connect	69
3.13.37.	reventix	70
3.13.38.	rgi VoIP Trunk 200	70
3.13.39.	R-Kom	71
3.13.40.	sipgate	71
3.13.41.	Steffel-Voice	72
3.13.42.	Tele AG	73
3.13.43.	TeleData	74
3.13.44.	Telekom CompanyFlex SIP Trunk	75
3.13.45.	Telekom IP-As mit MSN	76
3.13.46.	Telekom DeutschlandLAN SIP-Trunk Registered Mode	77
3.13.47.	TelemaxX	78
3.13.48.	Thüringer Netkom	79
3.13.49.	T-Systems Corporate SIP Trunk	79
3.13.50.	teliko	80
3.13.51.	TNG Stadtnetz	81
3.13.52.	Toplink	81
3.13.53.	Unitymedia	82
3.13.54.	Universe SIP Connect	83
3.13.55.	Vodafone Anlagenanschluss R4	84
3.13.56.	Vodafone Anlagenanschluss R5	85
3.13.57.	Vodafone Anlagenanschluss R6	86
3.13.58.	Voiceworks DE	87
3.13.59.	wilhelm.tel	88
3.13.60.	wittenberg-net GmbH	89
3.13.61.	WOBCOM	90
3.14.	Greece	91
3.14.1.	COSMOTE	91
3.15.	Hungary	92
3.15.1.	Netfone Telecom	92
3.16.	Hong Kong	93
3.16.1.	Hong Kong Broadband Network	93

3.16.2.	HGC	94
3.17.	Italy	95
3.17.1.	Broadcloud	95
3.17.2.	Infracom	95
3.17.3.	TWT	95
3.17.4.	Viatek	96
3.18.	Lichtenstein	96
3.18.1.	FL1 Telecom	96
3.19.	Luxembourg	96
3.19.1.	IPnexia	96
3.20.	Mexico	97
3.20.1.	Telefonica	97
3.21.	Netherlands	98
3.21.1.	BCOM	98
3.21.2.	BLU Networks	98
3.21.3.	Deanconnect B.V.	99
3.21.4.	gnTel	99
3.21.5.	infopact	100
3.21.6.	KPN VoiPConnect,	100
3.21.7.	KPN TLS NL (KPN EEN over TLS)	100
3.21.8.	Motto Communications	101
3.21.9.	OneCentral	101
3.21.10.	OneXS	101
3.21.11.	Pocos	101
3.21.12.	RoutIT	102
3.21.13.	RoutIT TLS	103
3.21.14.	Scaldis B.V.	103
3.21.15.	SIGNET B.V	104
3.21.16.	Speakup	105
3.21.17.	tele2	105
3.21.18.	T-Mobile	105
3.21.19.	Vodafone	106
3.21.20.	Voiceworks NL	106
3.21.21.	Voiceworks MEX	107
3.21.22.	VoipQ	107
3.21.23.	VoIPXS	108
3.21.24.	X2COM	108
3.21.25.	Ziggo	109
3.21.26.	Vodafone Ziggo	109
3.22.	New Zealand	110
3.22.1.	Orcon Ltd	110
3.22.2.	TelstraClear	110
3.22.3.	voyager	111
3.23.	Portugal	112
3.23.1.	Altice (Portugal Telecom)	112
3.23.2.	G9 Telecom	112
3.23.3.	Portugal Telecom	113
3.23.4.	Vodafone	113
3.24.	Saudi Arabia	114
3.24.1.	Saudi Telecom Company	114

3.25.	Serbia	115
3.25.1.	Orion Telekom	115
3.25.2.	Telenor	115
3.26.	Slovakia	116
3.26.1.	Slovak Telekom	116
3.27.	Slovenia	116
3.27.1.	A1 SIP Trunk	116
3.27.2.	Detel	116
3.27.3.	MegaM	117
3.27.4.	T-2	117
3.27.5.	Telemach	117
3.28.	South Africa	118
3.28.1.	Nashua NCN	118
3.28.2.	Vodacom	118
3.29.	Spain	119
3.29.1.	LCR	119
3.29.2.	Telecable	119
3.29.3.	vozelia	119
3.29.4.	VozTelecom	120
3.30.	Sweden	121
3.30.1.	Tele2	121
3.30.2.	Telia	121
3.31.	Switzerland	122
3.31.1.	E-fon AG	122
3.31.2.	Improware	122
3.31.3.	Nexphone	123
3.31.4.	Peoplefone AG (CH)	123
3.31.5.	phonestar*	124
3.31.6.	sipcall	124
3.31.7.	Sunrise	125
3.31.8.	Swisscom Enterprise SIP	126
3.31.9.	Swisscom Smart Business Communication	126
3.31.10.	Swisscom Smart Business Connect Internet Trunk	127
3.31.11.	Telco Pack SA	127
3.31.12.	UPC CH Internet Registration	128
3.31.13.	UPC CH Internet Static IP	129
3.31.14.	vtx	129
3.32.	United Kingdom	130
3.32.1.	Broadcloud	130
3.32.2.	BT IPVS	130
3.32.3.	BT Wholesale SIP Trunking	131
3.32.4.	BT Wholesale Hosted Communications	132
3.32.5.	Gamma	133
3.32.6.	KCOM	133
3.32.7.	TalkTalk	134
3.32.8.	tIPicall	134
3.32.9.	Vodafone	135
3.32.10.	VoiceFlex	135
3.32.11.	VoIP Ltd i-Line	135
3.33.	U.S.A.	136

3.33.1.	AT&T	136
3.33.2.	Broadcloud	136
3.33.3.	CenturyLink	136
3.33.4.	Fusion 360	137
3.33.5.	IPfone	137
3.33.6.	Intermedia.net Inc	138
3.33.7.	SoTel	139
3.33.8.	Windstream	139
3.33.9.	XO	139
Table of History		140

1. Introduction

The tables below provide an overview of tested ITSP providers for OpenScape Business.

It must be emphasized that the documented features represent the result when the test was finished.

Starting with OpenScape Business V3R4 certifications are released for

- OpenScape Business V3 Mainboard Familiy
- OpenScape Business S

Important Note:

It is highly recommended to check for the most current SW on SW-Download Server within the Unify Partner Portal.

For more information: osbiz-certification@mitel.com

2. Definition of Features

SIP DID Account

Provider supplies the customer with a range of call numbers for direct inward dialing, accessible with one or no SIP registration.

SIP Client Account

Provider supplies the customer with one or more single call numbers which are registered separately.

Multisite

Provider allows handling of numbers from different locations/areas via a single trunk (single registration) or dedicated trunks for each location/area (multiple registrations). For more info if each location/area needs a dedicated registration please check

<https://wiki.unify.com/images/7/71/MultiRegistrationForITSP.pdf>.

CLIP no Screening

Provider allows sending of calling party numbers different from the numbers assigned to the account (e.g. toll-free numbers 0800-, or original calling party number in case of call forwarding).

CLIP/CLIR

Calling line indication presentation / calling line indication restriction. Call numbers are displayed or suppressed in ringing state.

COLP

Connected line presentation / connected line restriction. Connected call numbers are displayed or suppressed in connected state.

Call Forwarding (302)

Provider support call forwarding (also referred as call deflection) initiated with a 302 response.

DTMF

Transmission of dual tone multi frequency signaling is used e.g. for voicemail or conference server access. RFC 2833 support is needed to control e.g. UC-Suite.

Codecs

G.711: 64 kbps coding, variants a-law and u-law

G.729: 8 Kbps coding, variants A and AB with silence insertion

G.722: the use of the G.722 codec must be enabled on the end devices with priority 1 (first line codec) and depends on the properties of the remote station.

For IP-IP calls other codecs (like G.722) can be negotiated between the endpoints. Negotiation of such codecs is supported by the OpenScape Business system.

FAX

T.38 protocol allows safe transmission also for multi-page documents. The option of sending or receiving T.38 faxes depends on the properties of the remote station.

Secure Trunk

Provider offers a secured SIP trunk (TLS transport and SRTP media).

3. ITSP Details

3.1. International

3.1.1. Broadcloud



Australia - France - Germany - Italy – United Kingdom - USA

System	OSBiz
Released with Version	V2R3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	ITSP support multiple call numbers from different areas in the same country on the same trunk
CLIP / CLIR	yes / yes
CLIP no Screening	no
COLP	-
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes

Remarks:

In a transit call forwarding scenario Broadcloud provides the number of the originating caller. E.g. external A calls internal B. B is forwarded to external C. C get the number information of A

During setup of the ITSP trunk in OpenScape Business the country specific server addresses needs to be configured in the Broadcloud profile.

3.1.2. COLT international

System	OSBiz
Supported since version	V1_R1.1.0
Provider (profiles see *1)	
SIP DID account	√ * 2
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

*1 = COLT VPN Access may need additional manual configuration)
COLT UK & Europe

*2 = no registration

3.1.3. Kwebbl SIP Trunk

Austria – Belgium – Germany – Netherlands – Switzerland



System	OpenScape Business
Released with Version	V3R4
<i>Kwebbl SIP Trunk</i>	Features & Capabilities
Account (DID/Client)	<i>DID</i>
Multisite	<i>yes - single trunk / dedicated trunk</i>
CLIP / CLIR	<i>yes / yes</i>
CLIP no Screening	<i>no</i>
COLP	<i>no</i>
Call Forwarding (302)	<i>no</i>
DTMF (RFC2833/4733)	<i>yes</i>
Codecs G.722/G.711/G729	<i>no / yes / no</i>
T.38 Fax	<i>no</i>
Secure trunk	<i>no</i>

Remarks:

OpenScape Business is not approved for the use of the T.38-Fax protocol on the **Kwebbl SIP Trunk** profile.

3.1.4. Skype connect international

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.1.5. Verizon international

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.1.6. Virtual-Call

Austria – Brazil – Germany – Spain – Switzerland – United Kingdom



System	OpenScape Business
Released with Version	V3R4
<i>Virtual-Call</i>	Features & Capabilities
Account (DID/Client)	<i>DID</i>
Multisite	<i>yes - dedicated trunk (multiple registration)</i>
CLIP / CLIR	<i>yes / yes</i>
CLIP no Screening	<i>no</i>
COLP	<i>no</i>
Call Forwarding (302)	<i>yes</i>
DTMF (RFC2833/4733)	<i>yes</i>
Codecs G.722/G.711/G729	<i>no / yes / no</i>
T.38 Fax	<i>yes</i>
Secure trunk	<i>no</i>

Remarks:

OpenScape Business requires call routing via the media unit bundles (RTP proxy) to be activated by **Virtual-Call**.

Option for Backup Routing of incoming calls in case of internet failure

CLIP no Screening requires to deactivate the Backup Routing option "Overriding Identity" by the **Virtual-Call** support.

Otherwise, the CLIP number is replaced with the main number.

The ability to send or receive T.38 faxes depends on the characteristics of the remote station and is only available for IP system connections with activated T.38 codec.

3.2. Australia

3.2.1. [AAPT SIP Connect](#)



System	OSBiz
Released with Version	V3R2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

3.2.2. [Broadcloud](#)

see [Broadcloud](#)

3.2.3. [Commander Primus](#)

System	OSBiz
Supported since version	V1_R3.1
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-(P)
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.2.4. engin

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.2.5. Internode

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.2.6. Spark Voice Connect SIP

System	OpenScope Business
Released with Version	V3R2.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no



3.3. Austria

3.3.1. A1 SIPtrunk - registrierend



System	OpenScape Business
Released with Version	V2R7
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	Yes ¹⁾
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks:

¹⁾ Clip no Screening needs to be activated by A1.

A1 delivers a "A1 Router" to the customer which is used to terminate the SIP trunk.

3.3.2. **Drei Business SIP Connect**



System	OpenScape Business
Released with Version	V3R3
Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk / dedicated trunk
CLIP / CLIR	yes
CLIP no Screening	yes ¹⁾
COLP	yes
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

Remarks:

¹⁾ CLIP no Screening can be booked optional

²⁾ UC-Fax is not released for **Drei Business SIP Connect**

3.3.3. Magenta Business Voice SIP

System	OpenScape Business
Released with Version	V3R3
Features & Capabilities	
Account (DID/Client)	DID/MSN
Multisite	yes - single trunk
CLIP / CLIR	yes
CLIP no Screening	yes - if ordered
COLP	yes
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no



Remarks:

SIP External must be changed to 5060. It is recommended to set the SIP port (internal) to 5070.

3.3.4. Kabelplus Business Phone

System	OSBiz
Supported since version	V2_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√



3.3.5. IP-Austria

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√ ¹⁾
Codecs G.711/G.729	√ / -
T.38 Fax	²⁾

1) Only Payload Type 101 supported -> System and SIP endpoints has to be configured accordingly

2) Only T.38 outbound supported. LX was tested with OSO-fax-server. FAX with G.711 only working properly with 10ms frame size

Service call 0900 generally not allowed with IPAustria

3.3.6. LinzAG City Voice

System	OSBiz
Supported since version	V2_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.3.7. [Net4You-Voice4Biz](#)



System	OpenScape Business
Released with Version	V3R3
Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk / dedicated trunk
CLIP / CLIR	yes
CLIP no Screening	yes ¹⁾
COLP	yes
Call Forwarding (302)	no ²⁾
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

Notes:

SIP-Trunk **Net4You-Voice4Biz** is released for:

- OpenScape Business V3 Mainboard Family
- OpenScape Business S

SIP Extern must be changed to 5060. It's recommended to change Port SIP (intern) to 5070.

¹⁾ CLIP no Screening needs to be booked

²⁾ Call Forwarding (302) of **Net4You-Voice4Biz** is not supported by OpenScape Business

3.3.8. [Neotel](#)

System	OSBiz
Supported since version	V2_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.3.9. Peoplefone AG

System	OSBiz
Supported since version	V2R6
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.3.10. SalzburgAG CableLink

System	OSBiz
Supported since version	V2_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.4. Belgium

3.4.1. Belgacom.IMS / Proximus

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√ *1
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

*1 = no SIP registration

UC-Suite is not yet released for Belgacom IMS

3.4.2. BCOM

for details on BCOM see the table BCOM

3.4.3. Destiny

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.4.4. BKM

Formerly named Hexacom



System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

Remarks:

With V3 a major update of the BKM profile is available.

BKM offers two types of trunks:

1. accessible via public network: for this type of trunk the profile could be used without changes
2. access via private link: for this type of access the settings need to be adapted, please check the configuration document

3.4.5. gnTel

for details on gnTel see the table gnTel



3.4.6. **IPnexia – Belgium - Luxemburg**



System	OSBiz
Released with Version	V2R6.2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

3.4.7. ORANGE



System	OSBiz
Released with Version	V3R2.1
profile	Orange BE S&F
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
COLP	no
CLIP no Screening	yes ¹⁾
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes

System	OSBiz
Released with Version	V3R2.1
profile	Orange BE SIP
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
COLP	no
CLIP no Screening	yes ¹⁾
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes

Remarks:

The registrar/proxy IP address will be different for each customer. Orange delivers a CPE device to the customer. This CPE device has typical an xDSL uplink to the providers SIP Trunk. The CPE does get an IP Address which is in the same subnet of the customer PBX. ITSP is reached via static route configured in OSBIZ. Please check the configuration guide. ISP is reached via different router.

¹⁾ In default the Orange profile has CLIP no Screening activated. The user must sign an agreement for CLIP no Screening. As long as the user has not signed the agreement with

Orange, forwarded calls will be rejected! If CLIP no Screening agreement is not signed the profile needs to be changed manually.

3.4.8. Proximus Enterprise Voice

System	OpenScape Business
Released with Version	V3R4.1
Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes – dedicated trunk
CLIP / CLIR	yes
CLIP no Screening	no
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G722/G711/G729	yes / yes / yes
T.38 Fax	no
Secure trunk	no



Remarks:

- Call Forwarding (302) is active per default
- UC-Fax is not released for **Proximus Enterprise Voice**

3.4.9. [Telenet](#)



System	OSBiz
Released with Version	V1R1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Remarks:

Customer specific profile entries are needed for domain name and Proxy.

3.4.10. [WIN](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√ *1)
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

*1) = no registration

UC-Suite is not yet released

3.4.11. [X2COM](#)

for details on X2COM see the table X2COM

3.5. Brazil

3.5.1. vivo



System	OSBiz
Released with Version	V2R7.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	-
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

Remarks:

Vivo provide 4 different link types.

Please check the configuration document about the necessary configuration steps:

Link 1,2 and 4 Customer specific profile entries are needed for domain and proxy.

Link 4: Customer specific profile entries are needed for domain, proxy and **inbound proxies**.

Static routes must be configured.

3.5.2. Voitel

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√ / -
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.6. Canada

3.6.1. BabyTEL

System	OSBiz
Supported since version	V2_R0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.7. Chile

3.7.1. ENTEL NGN

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.

3.8. Czech Republic

3.8.1. GTS

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.8.2. O2 CZ

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.8.3. T-mobile

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.9. Denmark

3.9.1. Global Connect

System	OSBiz
Supported since version	V1_R3.3
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.9.2. TDC DK

System	OSBiz
Supported since version	V2 R2.1.0_262
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√/-
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√
Multisite	-)*

*) Not supported by country

3.9.3. Telia



System	OSBiz
Released with Version	V2R2.2.0_279
ITSP Features & Capabilities	
Account (DID/Client)	DID ¹⁾
Multisite	-
CLIP / CLIR	yes / yes
COLP	-
DTMF (RFC2833/4733)	yes ²⁾
Codecs G711/G729	yes / -
T.38 Fax	- ³⁾

Remarks:

¹⁾ No registration is used, Port 5060 MUST be used for SIP traffic

²⁾ Only Payload Type 101 supported -> System and SIP endpoints has to be configured accordingly

³⁾ T.38 is not supported in default, it can be requested if needed

3.9.4. Uni-tel A/S

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / -
T.38 Fax	√

3.10.Finland

3.10.1. [Elisa](#)

Certification was renewed with new platform of Elisa (Elisa NGN) in January 2013.

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / -
T.38 Fax	√

3.10.2. [Länsilinkki](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / -
T.38 Fax	√

3.10.3. [TDC](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√ *1
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

*1) : no registration

3.10.4. [TeliaSonera](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.11.Estonia

3.11.1. [Telia](#)



System	OSBiz
Released with Version	V2R6.2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes, single registration
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks

Due to a problem with certain call scenarios a DSP board is needed to terminate the payload. See the configuration document for details.

Fax is not fully tested and not released.

3.12.France

3.12.1. [Bouygues](#)

System	OSBiz
Supported since version	V2_R1.0.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√/√
COLP	-
DTMF (RFC 2833)	√ ¹⁾
Codecs G.711/G.729	√ / √
T.38 Fax	√

¹⁾ Only Payload Type 101 supported -> System and SIP endpoints has to be configured accordingly

3.12.2. [Broadcloud](#)

see Broadcloud

3.12.3. [codepi](#)

System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes, single registration
CLIP / CLIR	yes / yes
CLIP no Screening	yes ¹⁾
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no



Remarks:

¹⁾ Clip no Screening needs to be booked at CODEPI

3.12.4. Complete!

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.12.5. Dstny



System	OpenScape Business
Released with Version	V3R3
Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes – single and dedicated trunk
CLIP / CLIR	yes / no
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

3.12.6. Foliateam Opérateur



System	OSBiz
Released with Version	V2R7.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks:

T.38 MUST be deactivated in the OpenScape Business system

3.12.7. Hexatel

System	OSBiz
Supported since version	V1_R3.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	-
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.12.8. IP Directions



System	OSBiz
Released with Version	V2R7
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

Remarks:

T.38 MUST be deactivated in the OpenScape Business system
Due to interoperability issues UC-Fax is not released with IP-Directions

3.12.9. IPnexia

for details on IPnexia see the table [IPnexia Belgium](#)



3.12.10. [Jaguar](#)



System	OSBiz
Released with Version	V2R7.1
ITSP Features & Capabilities	
Account (DID/Client)	DID ¹⁾
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	not supported ²⁾
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Remarks:

¹⁾ Special configuration of primary and secondary server needed, see configuration document for details.

²⁾ Jaguar requires a special signalling for Clip no Screening which is not supported by OpenScape business

3.12.11. [Keyyo](#)



System	OSBiz
Released with Version	V3R2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes / yes
CLIP no Screening	no
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

3.12.12. [MyStream](#)

System	<i>OSBiz</i>
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.12.13. [OpenIP](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / -
T.38 Fax	-

3.12.14. [Orange Business Services SIP trunking](#)



**Business
Services**

System	OSBiz
Released with Version	V2R4.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
COLP	no
CLIP no Screening	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / partly
T.38 Fax	yes
Secure trunk	no

Remarks:

To comply with the requirements of the Orange Business Services SIP trunk a special setup of OpenScape Business is needed. Please read the configuration description available in the Wiki. Customer specific profile entries are needed for domain name and proxy address

Special configuration is needed for the following parameters:

- EXT_SIP_PORT **MUST** be configured with 5060 (default is 5070)
- RFC 2833 payload type **MUST** be 101
- RFC 2198 support **MUST** be disabled
- G.729AB is NOT supported by ORANGE and **SHOULD** be disabled

3.12.15. Paritel Operateur



System	OSBiz
Released with Version	V1R1
ITSP Features & Capabilities	
Account (DID/Client)	DID / Client
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	no
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

3.12.16. Sewan Communications

System	OSBiz
Supported since version	V1_R3.3.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.13. Germany

3.13.1. 1&1

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	√/ √
T.38 Fax	-

3.13.2. 1&1 Versatel



System	OSBiz
Released with Version	V2R4.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
COLP	-
CLIP no Screening	yes ¹⁾
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes ²⁾
secure trunk	no

Remarks:

¹⁾ CLIP no screening needs to be configured on the 1&1 Versatel platform

²⁾ **UC-Fax is not released with 1&1 Versatel** (This needs an enhancement in OpenScape Business and will be released in an upcoming version)

3.13.3. [autphone](#)



System	OSBiz
Released with Version	V2R7
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes ¹⁾
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Remarks:

¹⁾ CLIP no Screening needs to be booked at ITSP

3.13.4. [Broadcloud](#)

see [Broadcloud](#)

3.13.5. BITel



System	OSBiz
Released with Version	V2R6.2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks:

BITel delivers an access device, IP address of access device needs to be configured as Proxy and Registrar

¹⁾ Clip no Screening needs to be booked at BITel

System	OpenScape Business
Released with Version	V3R3
BITel Business SIP Flex	Features & Capabilities
Account (DID/Client)	<i>DID</i>
Multisite	<i>no</i>
CLIP / CLIR	<i>yes</i>
CLIP no Screening	<i>yes</i>
COLP	<i>no</i>
Call Forwarding (302)	<i>yes</i>
DTMF (RFC2833/4733)	<i>yes</i>
Codecs G711/G729	<i>yes / no</i>
T.38 Fax	<i>yes</i>
Secure trunk	<i>no</i>

Remarks:

SIP-Trunk **BITel Business SIP Flex** is released for:

- OpenScape Business V3 Mainboard Family
- OpenScape Business S

3.13.6. [Date!](#)



System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID ¹⁾
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
CLIP no Screening	yes ²⁾
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
secure trunk	no

Remarks:

¹⁾ The certification is valid for the DATEL Phone&Surf SIP Trunk product. Other products (e.g. MSN based) are available but not yet certified with OpenScape Business

²⁾ Clip no Screening needs to be booked at DATEL

3.13.7. Deutsche Telefon



System	OSBiz
Released with Version	V2R3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes – single trunk / dedicated trunks
CLIP / CLIR	yes / yes
COLP	-
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / -
T.38 Fax	yes

Remarks:

"Einzelverbindungsnaehweis": The number presented in PAI will be used in the EVN. If the individual number should be presented in EVN the CLIP no Screening feature must be deactivated.

3.13.8. [easybell](#)



System	OSBiz
Released with Version	V2R6
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes ¹⁾
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks:

¹⁾ CLIP no screening must be activated in customer portal of easybell (see configuration description)

Changed default settings introduced in V2R7, please check the configuration document for details (CLIPnoScreening)

3.13.9. EasyFone



System	OSBiz
Released with Version	V3R2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunks
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	optional
secure trunk	no

Remarks:

- The EasyFone SIP Trunk requires a static public IP address.
- The possibility of sending or receiving T.38 faxes depends on the characteristics of the remote station and the transmission may take place with G.711.
- Automatic use of the backup SIP trunk is currently not supported.

3.13.10. ecotel sipTrunk 2.0



System	OSBiz
Released with Version	V3R1.2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes / yes
CLIP no Screening	yes ¹⁾
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks:

¹⁾ CLIP no screening needs to be booked

3.13.11. [ennit](#)

Profile maintained for existing installations.

A new profile with updated settings is available "TNG Stadtnetz"

3.13.12. [envia TEL](#)



System	OpenScape Business
Released with Version	V3R2
<i>envia TEL enVoice IP range</i>	Features & Capabilities
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes
CLIP no Screening	yes ¹⁾
COLP	yes
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711	yes
Codecs G729	no
T.38 Fax	no
Secure trunk	no

Anmerkungen:

¹⁾ CLIP no Screening ist ein kostenpflichtiges Leistungsmerkmal und muss gesondert beauftragt werden. Die Nutzung ist im Profil voreingestellt.

3.13.13. [equada](#)

System	OSBiz
Supported since version	V2_R0.3.11 24
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / -
T.38 Fax	√

3.13.14. [ewe](#)

The profile is valid for **EWE** (<https://www.ewe.de/>), **swb** (<https://www.swb.de/>) and **osnatel** (<https://www.osnatel.de/>).



System	OpenScape Business
Released with Version	V2R6
update	V3R3
EWE Voice+ SIP Trunk	Features & Capabilities
Account (DID/Client)	<i>DID</i>
Multisite	<i>dedicated trunk ¹⁾</i>
CLIP / CLIR	<i>yes / yes</i>
CLIP no Screening	<i>yes ²⁾</i>
COLP	<i>yes</i>
Call Forwarding (302)	<i>yes</i>
DTMF (RFC2833/4733)	<i>yes</i>
Codecs G722/G711/G729	<i>yes /yes / no</i>
T.38 Fax	<i>yes ³⁾</i>
Secure trunk	<i>yes</i>

Remarks:

¹⁾ Depending on customers Call Attempts per Second „Multisite“ is available for a second trunk and requires confirmation of EWE TEL GmbH.

²⁾ Clip no Screening needs to be activated by the provider.

³⁾ T.38 is support in transport mode only. If a destination supports T.38 fax will be transported in T.38, if interworking to TDM is needed or destination does not support T.38 the fax is transmitted by G.711.

3.13.15. [Gamma](#)



System	OpenScape Business
Released with Version	V3R3
Gamma NGN (DE)	Features & Capabilities
Account (DID/Client)	<i>DID</i>
Multisite	<i>yes - dedicated trunk</i>
CLIP / CLIR	<i>yes / yes</i>
CLIP no Screening	<i>yes</i>
COLP	<i>no</i>
Call Forwarding (302)	<i>no</i>
DTMF (RFC2833/4733)	<i>yes</i>
Codecs G711/G729	<i>yes / no</i>
T.38 Fax	<i>yes</i>
Secure trunk	<i>no</i>

Remarks:

T.38 is not released with OpenScape Business V3R3.

3.13.16. [gmx](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / ?
T.38 Fax	-

3.13.17. [gnTel](#)

for details on gnTel see the table [gnTel](#)



3.13.18. [GVG Glasfaser](#)

System	OpenScape Business
Released with Version	V3R4.1
Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes
CLIP no Screening	yes ¹⁾
COLP	no
Call Forwarding (302)	yes ²⁾
DTMF (RFC2833/4733)	yes
Codecs G722/G711/G729	yes / yes / no
T.38 Fax	yes
Secure trunk	no



Remarks:

¹⁾ CLIP no Screening is optional and needs to be booked

²⁾ Call Forwarding (302) is active per default

3.13.19. [Helinet](#)



System	OpenScape Business
Released with Version	V3R3
Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes
CLIP no Screening	yes ¹⁾
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks:

¹⁾ CLIP no Screening can be booked optionally.

3.13.20. [herweck callamar](#)



System	OpenScape Business
Released with Version	V3R4
callamar	Features & Capabilities
Account (DID/Client)	<i>DID</i> ¹⁾
Multisite	<i>no</i>
CLIP / CLIR	<i>yes / yes</i>
CLIP no Screening	<i>yes</i>
COLP	<i>no</i>
Call Forwarding (302)	<i>yes</i>
DTMF (RFC2833/4733)	<i>yes</i>
Codecs G.722/G.711/G729	<i>no / yes / yes</i> ²⁾
T.38 Fax	<i>yes</i>
Secure trunk	<i>no</i>

Remarks:

¹⁾ Emergency calls are forwarded based on the number of the calling subscriber and must be set up in the callamar Provisioning Portal.

²⁾ G.729 can be booked optionally.

3.13.21. [HL komm](#)



System	OSBiz
Released with Version	V2R3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
CLIP no Screening	yes ¹⁾
COLP	-
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / -
T.38 Fax	-
Secure trunk	no

3.13.22. [http](#)



System	OSBiz
Released with Version	V2R6.2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	??
CLIP / CLIR	yes / yes
CLIP no Screening	yes ¹⁾
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

Remarks:

http delivers an access device, IP address of access device needs to be configured as Proxy and Registrar

¹⁾ Clip no Screening needs to be booked at http.

System	OpenScape Business
Released with Version	V3R3
Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes
CLIP no Screening	yes
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

Remarks:

http Business Flex SIP-Trunk smart is released for following OpenScape Business variants:

- OpenScape Business V3 Mainboard Familiy
- OpenScape Business S

3.13.23. [Inexio](#)



System	OSBiz
Released with Version	V2R5.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

3.13.24. [komroVoIP-Trunk](#)

System	OpenScape Business
Released with Version	V3R3
Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes
CLIP no Screening	yes ¹⁾
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes ²⁾
Secure trunk	no



Remarks:

¹⁾ CLIP no Screening can be booked optional

²⁾ The option of sending or receiving T.38 faxes depends on the properties of the remote station and is only available within the komro network and only for IP system connections with an activated T.38 codec.

3.13.25. M-Net Premium



System	OpenScape Business
Released with Version	V3R3.2 (update)
M-net Premium SIP-Trunk Capabilities	Features &
Account (DID/Client)	<i>DID</i>
Multisite	<i>yes - single trunk</i>
CLIP / CLIR	<i>yes</i>
CLIP no Screening	<i>yes ¹⁾</i>
COLP	<i>no</i>
Call Forwarding (302)	<i>yes</i>
DTMF (RFC2833/4733)	<i>yes</i>
Codecs G.722/G.711/G.729	<i>yes ²⁾ / yes / optional</i>
T.38 Fax	<i>yes</i>
Secure trunk	<i>yes ³⁾</i>

Anmerkungen:

¹⁾ CLIP no Screening kann optional gebucht werden.

²⁾ Die Verwendung des Codecs G.722 ist mit der Priorität 1 an den Endgeräten freizugeben (first line codec). Die Nutzung von G.722 ist abhängig von den Eigenschaften der Gegenstelle (Endgerät, IP-Anlagen-Anschluss, ...) und für folgende OpenScape Business Varianten freigeben:

- OpenScape Business V3 Mainboard Family
- OpenScape Business S

³⁾ Die Zertifikate werden von **M-net** zur Verfügung gestellt und sind in die OpenScape Business zu importieren. Der Codec G.722 wird in der Betriebsart „Sicherer Trunk“ nicht unterstützt.

Es ist ein manueller Profilupdate erforderlich: „Media Renegotiation Avoidance“: deaktiv.

3.13.26. [MK Netzdienste](#)



System	OSBiz
Released with Version	V2R6.2 (update)
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	?
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Remarks:

Clip no Screening needs to be booked at provider.

3.13.27. NetCologne ProPhone SIP



System	OSBiz
Released with Version	V2R7
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

Remarks:

OpenScape Business must be connected with a dedicated VoIP router using the WAN interface in TCP/IP mode. Internet traffic needs to be routed via a different router. See the configuration description for details.

3.13.28. NetCom BW



System	OSBiz
Released with Version	V2R6
ITSP Features & Capabilities	
Account (DID/Client)	DID ¹⁾
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks:

¹⁾ = without registration

Netcom BW delivers an access device, the IP-address of the access device needs to be configured, thus the profile needs to be completed during configuration of the system

For security reasons OpenScape Business uses dedicated SIP server ports for internal (5060) and external (5070) traffic. To ensure symmetric UDP traffic without registration the external SIP port in Openscape Business MUST be configured to 5060.

UC is not tested and released with Netcom BW

3.13.29. [NFON](#)



System	OSBiz
Released with Version	V2R3.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no yet available / coming soon
CLIP / CLIR	yes / yes
COLP	no
CLIP no Screening	yes
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes

3.13.30. O2 All-IP Voice SIP



System	OSBiz
Released with	V2R2.2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	multiple registration performed by CNG
CLIP / CLIR	yes / yes
COLP	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	_1)

Remarks:

O₂ delivers a Corporate Network Gateway (CNG) which is used to terminate the SIP trunk. OpenScape Business cannot be connected directly without CNG (using the O₂ Gm-Interface)

OpenScape Business must be connected with the CNG using the WAN interface in TCP/IP mode.

During setup of the ITSP trunk the customer specific CNG IP address needs to be configured in OpenScape Business.

For security reasons OpenScape Business uses dedicated SIP server ports for internal (5060) and external (5070) traffic. The CNG can handle SIP traffic on port 5060 only. Due to this limitation, the external SIP port in OpenScape Business **MUST** be configured to 5060.

¹⁾ T.38 is support in transport mode only. If a destination supports T.38 fax will be transported in T.38, if interworking to TDM is needed or destination does not support T.38 the fax is transmitted by G.711

3.13.31. [omnidat](#)



System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	<i>yes (registration for each location)</i>
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

Remarks:

Clip no Screening needs to be booked and payed:

3.13.32. [Peoplefone AG \(DE\)](#)

System	OSBiz
Supported since version	V2_R0.3.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.13.33. [PhoneVoice](#)



System	OSBiz
Released with Version	V2R5
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

3.13.34. [purstel](#)



System	OSBiz
Released with Version	V2R7.1 (update)
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	Yes ¹⁾
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no T.38 Fax service stopped on 01.01.2020
Secure trunk	no

Remarks:

Customer specific profile entries are needed for Domain name, Registrar and Proxy.

¹⁾ CLIP no screening must be activated in customer portal

3.13.35. Plusnet IPfonie Extended

plusnet

System	OSBiz
Supported since version	QSC: V1_R1.1.0 Plusnet: V2R7
Provider	
IPfonie (DID)	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

Plusnet IPfonie extended replaces the previously used QSC profile which is not longer available.

3.13.36. Plusnet IPfonie Extended Connect

plusnet

System	OSBiz
Released with Version	QSC: V1R3.1 Plusnet: V2R7
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes (single registration)
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes ¹⁾
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	yes (but not yet released)

Remarks:

¹⁾ Only Payload Type 101 supported -> System and SIP endpoints **MUST** be configured accordingly

Plusnet has taken over all activities from QSC AG. By end of 2019 Plusnet is no longer allowed to use the QSC brand. Thus, new profiles are available in OpenScape Business. Please check the configuration document and the information you have received from Plusnet.

3.13.37. [reventix](#)



System	OSBiz
Released with Version	V2R6.2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes ¹⁾
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

Remarks:

¹⁾ Depending on customer needs one or several registrations are used.

3.13.38. [rgi VoIP Trunk 200](#)



System	OSBiz
Released with Version	V3R1.2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

3.13.39. R-Kom



System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes (needs to be payed)
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

3.13.40. sipgate

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
sipgate trunking (DID)	√
sipgate basic (MSN)	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.13.41. Steffel-Voice



System	OSBiz
Released with Version	V2R7.1 (update)
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Remarks:

Clip no Screening need to be configured/booked at ITSP.

3.13.42. Tele AG



System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID ¹⁾
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
CLIP no Screening	yes ²⁾
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks:

¹⁾ The certification is valid for the Tele AG SIP Trunk product. Other products (e.g. MSN based) are available but not yet certified with OpenScape Business.

²⁾ Clip no Screening needs to be booked at Tele AG

3.13.43. TeleData



System	OSBiz
Released with Version	V2R5.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
CLIP no Screening	yes ¹⁾
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	no ²⁾
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

Remarks:

¹⁾ optional feature, needs to be booked at TeleData

²⁾ TeleData does not provide media gateways, thus the support of RFC2833 telephone events depends on the connection partner. **UC-Suite cannot be released with this ITSP.**

3.13.44. Telekom CompanyFlex SIP Trunk



System	OSBiz
Released with Version	V2R7.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
CLIP no Screening	yes ¹⁾
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	yes

Remarks:

¹⁾ Clip no Screening needs to be booked at ITSP (please check configuration document)

The Telekom CompanyFlex SIP-Trunk profile is also suitable for the *T-Systems Corporate CompanyFlex* product offered by T-Systems as all trunks are operated on the same platform:

3.13.45. Telekom IP-As mit MSN



System	OSBiz
Supported since version	V1_R2.1
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-(P)

The *Telekom IP-As mit MSN* profile is suitable for the following products offered by Telekom and T-Systems as all trunks are operated on the same platform:

3.13.45.1. Telekom DeutschlandLAN IP Start

3.13.45.2. Telekom DeutschlandLAN IP Voice/Data

3.13.45.3. T-Systems Corporate call Start

3.13.45.4. T-Systems Corporate IP Voice/Data

3.13.46. Telekom DeutschlandLAN SIP-Trunk Registered Mode



System	OSBiz
Released with Version	V2R2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
COLP	no
CLIP no Screening	yes (with costs)
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes ²⁾
Secure Trunk	yes

Remarks:

¹⁾ T.38 is support in transport mode only. If a destination supports T.38 fax will be transported in T.38, if interworking to TDM is needed or destination does not support T.38 the fax is transmitted by G.711

The Telekom DeutschlandLAN SIP-Trunk profile is suitable for the following products offered by T-Systems as all trunks are operated on the same platform.

3.13.47. [TelemaxX](#)



System	OSBiz
Released with Version	V3R0.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	yes

Remarks:

TelemaxX delivers an access device which must be connected to the WAN interface. Please check the configuration hints about static route configuration.

3.13.48. Thüringer Netkom



System	OpenScape Business
Released with Version	V3R4.1
Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes
CLIP no Screening	yes ¹⁾
COLP	no
Call Forwarding (302)	yes ²⁾
DTMF (RFC2833/4733)	yes
Codecs G722/G711/G729	no / yes / no
T.38 Fax	no
Secure trunk	no

Remarks:

¹⁾ CLIP no Screening is optional and needs to be booked

²⁾ Call Forwarding (302) is active per default

3.13.49. T-Systems Corporate SIP Trunk



Individual profile for the specific customer requirements based on a Project Specific Release.

Please contact: OSBiz-certification@mitel.com.

3.13.50. [teliko](#)



System	OSBiz
Released with Version	V2R7.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes ¹⁾
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no ²⁾
Secure trunk	no

Remarks:

¹⁾ Clip no Screening need to be booked at Teliko

²⁾ For best interoperability T.38 MUST be deactivated in the OpenScape Business system

3.13.51. [TNG Stadtnetz](#)



System	OSBiz
Released with Version	V2R7
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes ¹⁾
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

Remarks:

¹⁾ Call deflection needs to be booked at TNG

Profile is used for different carriers; thus domain, proxy and registrar need to be configured manually. See configuration description.

TNG must configure "national number format" of calling party for incoming local calls. The TNG default of "local number format" is not supported by OpenScape Business.

3.13.52. [Toplink](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.13.53. Unitymedia



System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes ¹⁾
T.38 Fax	yes
Secure trunk	no

Remarks:

¹⁾ G729 only endpoints are not supported due to problems with transfer scenarios.

System	OpenScape Business
Released with Version	V3R3.1(update)
Universe SIP Connect	Features & Capabilities
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes
CLIP no Screening	yes ¹⁾
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G.722/G.711/G.729	yes ²⁾ / yes / no ³⁾
T.38 Fax	no ³⁾
Secure trunk	yes ⁴⁾

Anmerkungen:

¹⁾ CLIP no Screening ist für die Anzeige des A-TIn bei Anrufumleitung freigegeben. Die Verwendung von Servicerufnummern (wie beispielsweise 0800..., 0900...) ist nicht freigegeben.

²⁾ Die Verwendung des Codecs G.722 ist mit der Priorität 1 an den Endgeräten freizugeben. Die Nutzung von G.722 ist abhängig von den Eigenschaften der Gegenstelle (Endgerät, IP-Anlagen-Anschluss, ...) und für folgende OpenScape Business Varianten freigegeben:

- OpenScape Business V3 Mainboard Family
- OpenScape Business S

³⁾ Die Codecs G.729 und T.38 werden nicht unterstützt und sind in der OpenScape Business zu deaktivieren.

⁴⁾ Die Zertifikate werden von **Firstcom Europe AG** zur Verfügung gestellt und sind in die OpenScape Business zu importieren. Der Codec G.722 wird in der Betriebsart „Sicherer Trunk“ nicht unterstützt.

3.13.55. Vodafone Anlagenanschluss R4



System	OSBiz
Released with Version	V2R7 update with V3R2
ITSP Features & Capabilities	
Account (DID/Client)	DID ¹⁾
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	optional ²⁾ only for SIP end-to-end connections
Secure trunk	yes ³⁾

Remarks:

¹⁾ without registration

²⁾ The option of sending or receiving T.38 faxes depends on the properties of the remote station and is only available within the Vodafone network and only for IP system connections with an activated T.38 codec. T.38 in conjunction with encryption is not practically possible since T.38 terminals generally use UDPTL and not RTP.

³⁾ requires manual setting in expert mode (since V3R2)

Vodafone will use customer specific server addresses; thus the profile needs to be completed during configuration of the system

For security reasons OpenScape Business uses dedicated SIP server ports for internal (5060) and external (5070) traffic. You have to either request the usage of port 5070 at Vodafone or configure the external SIP port = 5060 in OpenScape Business.

Please check the configuration description available in Wiki.

3.13.56. Vodafone Anlagenanschluss R5



System	OpenScape Business
Released with Version	V3R3
Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes
CLIP no Screening	yes
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes
T.38 Fax	optional only for SIP end-to-end connections
Secure trunk	yes

Remarks:

The option of sending or receiving T.38 faxes depends on the properties of the remote station and is only available within the Vodafone network and only for IP system connections with an activated T.38 codec. T.38 in conjunction with encryption is not practically possible since T.38 terminals generally use UDPTL and not RTP.

3.13.57. Vodafone Anlagenanschluss R6



System	OpenScape Business
Released with Version	V3R4.1
Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes
CLIP no Screening	yes
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G722/G711/G729	yes
T.38 Fax	optional only for SIP end-to-end connections
Secure trunk	yes

Remarks:

The option of sending or receiving T.38 faxes depends on the properties of the remote station and is only available within the Vodafone network and only for IP system connections with an activated T.38 codec. T.38 in conjunction with encryption is not practically possible since T.38 terminals generally use UDPTL and not RTP.

3.13.58. [Voiceworks DE](#)



System	OSBiz
Released with Version	V3R1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes /no
T.38 Fax	yes
Secure trunk	no

3.13.59. wilhelm.tel



System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no ¹⁾
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no ²⁾
Secure trunk	no

Remarks:

- ¹⁾ 302 is supported by wilhelm.tel but the required signaling variant (different call number formats in 302 and basic call) is not supported by OpenScape Business
- ²⁾ T.38 MUST be deactivated in the system (see configuration document)

3.13.60. [wittenberg-net GmbH](#)

System	OpenScape Business
Released with Version	V3R3
wittenberg-net GmbH	Features & Capabilities
Account (DID/Client)	<i>DID</i>
Multisite	<i>yes - dedicated trunk</i>
CLIP / CLIR	<i>yes</i>
CLIP no Screening	<i>yes ¹⁾</i>
COLP	<i>yes</i>
Call Forwarding (302)	<i>yes</i>
DTMF (RFC2833/4733)	<i>yes</i>
Codecs G711/G729	<i>yes / no</i>
T.38 Fax	<i>no</i>
Secure trunk	<i>no</i>



Remarks:

¹⁾ CLIP no Screening is optional and can be booked to show the calling party number with call forwarding.

Call data is recorded centrally for the account.

3.13.61. WOBCOM



System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID ¹⁾
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes ²⁾
Codecs G711/G729	yes / no
T.38 Fax	no ³⁾
Secure trunk	no

Remarks:

- ¹⁾ WOBCOM offers DID (Anlagenanschluß) and MSN (Teilnehmeranschluß) type of trunks. The certification is valid for the DID type only.
- ²⁾ RFC2833 is randomly supported. RFC2833 was not offered in several testcases during certification testing, thus UC is not released with WOBCOM. Please check the configuration document for limitations.
- ³⁾ T.38 must be deactivated in the system

3.14. Greece

3.14.1. COSMOTE



System	OSBiz
Supported since version	V2_R2.0.1_251
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√
Multisite	-1)

1): Not supported by the country specifications

3.15.Hungary

3.15.1. [Netfone Telecom](#)



System	OSBiz
Released with Version	V2R5.1
ITSP Features & Capabilities	
Account (DID/Client)	Client
Multisite	yes
CLIP / CLIR	yes/ yes ¹⁾
CLIP no Screening	no
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no ²⁾
Secure trunk	no

Remarks:

¹⁾ CLIR is supported through service code towards ITSP.

²⁾ T.38 is not supported by Netfone and MUST be deactivated in the system.

3.16.Hong Kong

3.16.1. [Hong Kong Broadband Network](#)



System	OSBiz
Released with Version	V2R3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	
CLIP / CLIR	√ / - ¹⁾
COLP	-
DTMF (RFC2833/4733)	√
Codecs G711/G729	√ / √
T.38 Fax	√ ²⁾

Remarks:

¹⁾ CLIR settings in profile are set properly, however provider ignores them at the moment and use another way to activate the CLIR for outgoing calls. See configuration example

²⁾ Problem with UC fax calls when other party has ECM enabled. Although the negotiation in T38 is done with ECM off, it looks that somehow ITSP still expects (ECM). Investigated in ITSP side. When ECM is disabled at other side, then problem is not occurring any more.

3.16.2. [HGC](#)



System	OSBiz
Released with Version	V2R5
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes ¹⁾
CLIP no Screening	no
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes ²⁾
T.38 Fax	no ³⁾
Secure trunk	no

Remarks:

¹⁾ CLIR is supported only with dialing the prefix '133' in front of the external number.

²⁾ Officially ITSP is not supporting G.729 (annexb=no) but can be offered under customer specific request. Codec is still available in SDP.

³⁾ T38 is not officially supported. However, for incoming Fax calls, OSBiz renegotiates for T38 and ITSP may accept it.

Please read the configuration documentation for the following special settings required for correct operation :

- VAD MUST be activated for all codes at VoiceGateway settings
- Redundant Transmission of RFC2833 MUST be disabled (default since V2R5)
- SIP_EXT port MUST be changed to 5061
- Incoming call To header conveys only the subscriber number

3.17.Italy

3.17.1. [Broadcloud](#)

see [Broadcloud](#)

3.17.2. [Infracom](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	√
DTMF (RFC 2833)	-
Codecs G.711/G.729	√ / -
T.38 Fax	-

Note:

There is an open issue with displaying international number format. Display, caller list and callback are not working correctly, because provider is not sending this in standard format.

3.17.3. [TWI](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	√ / -
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / -
T.38 Fax	√

3.17.4. [Viatek](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√ *1)
SIP Client account	√ *1)
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

*1) manual configuration of SIP server addresses necessary

3.18.Lichtenstein

3.18.1. [FL1 Telecom](#)

System	OSBiz
Supported since version	V2_R2.0.0
Provider	
SIP DID account	√ *1)
SIP Client account	
Features	
CLIP / CLIR	√/√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√
Multisite	√ *2)

*1) manual configuration of SIP server addresses necessary

*2) Supported, single registration can handle all sites (but not tested)

3.19.Luxembourg

3.19.1. [IPnexia](#)

for details on IPnexia see the table IPnexia Belgium



3.20.Mexico

3.20.1. [Telefonica](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.

3.21.Netherlands

3.21.1. [BCOM](#)



System	OSBiz
Released with Version	V2R1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes (since V2R5.1)
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

3.21.2. [BLU Networks](#)



System	OSBiz
Released with Version	V2R2 / update in V2R7
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Remarks:

Profile update with V2R7

3.21.3. [Deanconnect B.V.](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.21.4. [gnTel](#)



System	OSBiz
Released with Version	V2R3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	Yes / single registration for all sites 1)
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes 2)
T.38 Fax	yes
Secure trunk	Not yet released with OSBiz

Remarks:

- 1) Emergency calls are routed based on the calling party number
- 2) G.729 is available as an option which needs one time payment

3.21.5. [infopact](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	

3.21.6. [KPN VoiPConnect,](#)



System	OSBiz
Supported since version	V2 R2.1.0_262
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√/√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / -
T.38 Fax	√

3.21.7. [KPN TLS NL \(KPN EEN over TLS\)](#)



System	OSBiz
Released with Version	V3R1.2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	yes

3.21.8. [Motto Communications](#)

System	OSBiz
Supported since version	V2_R1
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√/√
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

Note: G722 is supported by ITSP

3.21.9. [OneCentral](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

Note:

OneCentral is released for SIP MEX feature (available only in OSBiz since V1R3.4 and later sw version)

3.21.10. [OneXS](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.21.11. [Pocos](#)



System	OSBiz
Released with Version	V3R1.2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

3.21.12. [RoutIT](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ /-
T.38 Fax	√

3.21.13. [RoutIT TLS](#)



System	OpenScape Business
Released with Version	V3R3
Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	yes

3.21.14. [Scaldis B.V.](#)



System	OSBiz
Released with Version	V3R1.2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

3.21.15. SIGNET B.V

System	OSBiz
Supported since version	V2_R2.0.1_251
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√/√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ /√
T.38 Fax	√
Multisite	√

3.21.16. [Speakup](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.21.17. [tele2](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.21.18. [T-Mobile](#)

System	OSBiz
Supported since version	V2_R0.3.1124
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.21.19. [Vodafone](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	√
DTMF (RFC 2833)	√-
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.21.20. [Voiceworks NL](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / -
T.38 Fax	-

3.21.21. [Voiceworks MEX](#)



System	OSBiz
Released with Version	V2R3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	Yes / supported with single registration
CLIP / CLIR	yes / not relevant ¹⁾
COLP	-
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	not relevant ¹⁾

Remarks:

Mobile phone integration with SIP-MEX

¹⁾ The certification is done with SIP-MEX in a mode where only SIP-MEX users could use the ITSP route. Consequently, some features (like CLIR) or calls (like fax calls) were unable to be set/used and were not relevant.

3.21.22. [VoipQ](#)



System	OSBiz
Released with Version	V3R0.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes ¹⁾
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

Remarks:

¹⁾ deactivated in default, need to be booked at provider

3.21.23. [VoIPXS](#)



System	OSBiz
Released with Version	V2R5
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	Yes / single registration for all sites ¹⁾
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes ²⁾
T.38 Fax	yes
Secure trunk	Not yet released with OSBiz

Remarks:

¹⁾ Emergency calls are routed based on the calling party number

²⁾ G.729 is available as an option which needs onetime payment

3.21.24. [X2COM](#)



System	OSBiz
Released with Version	V2R1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes (since V2R5.1)
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

3.21.25. [Ziggo](#)

System	OSBiz
Supported since version	V1_R3.2
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / -
T.38 Fax	√

Ziggo is available for existing installations. The profile should not be used for new installations

3.21.26. [Vodafone Ziggo](#)



System	OSBiz
Released with Version	V2R5.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no ¹⁾
Secure trunk	no

Remarks:

¹⁾T.38 is not supported by Vodafone Ziggo and MUST be deactivated in the system.

3.22.New Zealand

3.22.1. [Orcon Ltd](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.22.2. [TelstraClear](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / -
T.38 Fax	-

3.22.3. [voyager](#)



System	OSBiz
Released with Version	V2R7
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

Remarks:

Customer specific profile entries are needed for domain, registrar and proxy.

3.23.Portugal

3.23.1. [Altice \(Portugal Telecom\)](#)



System	OSBiz
Released with Version	V2R6
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	no
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Remarks:

For security reasons OpenScape Business uses dedicated SIP server ports for internal (5060) and external (5070) traffic. Altice handle SIP traffic on port 5060 in default, thus the external SIP port in Openscape Business MUST be configured to 5060. Please check the configuration document.

3.23.2. [G9 Telecom](#)



System	OSBiz
Released with Version	V3R2.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

3.23.3. [Portugal Telecom](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√ / -
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.

3.23.4. [Vodafone](#)



System	OpenScape business
Released with Version	V2R5
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes ¹⁾
CLIP / CLIR	yes / yes
COLP	no
CLIP no screening	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no ¹⁾
Secure trunk	no

Remarks:

¹⁾ Vodafone can give different numbers from different locations in one single registration

²⁾ T.38 is not supported by Vodafone and MUST be deactivated in the system

Vodafone will use customer specific server addresses, thus the profile needs to be completed during configuration of the system

3.24.Saudi Arabia

3.24.1. Saudi Telecom Company

System	OSBiz
Released with Version	V2R6
ITSP Features & Capabilities	
Account (DID/Client)	DID ¹⁾
Multisite	no
CLIP / CLIR	yes ²⁾ / yes
CLIP no Screening	no
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

Remarks:

¹⁾ No registration is used

²⁾ the calling party is represented in implicit format for national and international calls, for that reason international calls are presented with the wrong prefix in caller list and applications

Customer specific profile entries are needed for proxy address.

For security reasons OpenScape Business uses dedicated SIP server ports for internal (5060) and external (5070) traffic. STC handle SIP traffic on port 5060 in default, thus the external SIP port in Openscape Business MUST be configured to 5060. Please check the configuration guide for details

UC is not tested and released with STC.

3.25.Serbia

3.25.1. [Orion Telekom](#)

System	OSBiz
Supported since version	V1_R3.2.0
Provider	
SIP DID account	√ *1)
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

*1) without registration

3.25.2. [Telenor](#)

System	OSBiz
Supported since version	V1_R3.3.0
Provider	
SIP DID account	√ *1)
SIP Client account	-
Features	
CLIP / CLIR	√ / -
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

*1) without registration

3.26.Slovakia

3.26.1. Slovak Telekom

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√ *1)
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

1) without registration

Restrictions from Certification:

Semi-Attended Transfer with 2 PSTN fails -> ITSP error

No MoH when SIP holds PSTN fails -> ITSP error

3.27.Slovenia

3.27.1. A1 SIP Trunk

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.27.2. Detel

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.27.3. MegaM

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	√ / √
T.38 Fax	-

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.

3.27.4. T-2

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	√ / √
T.38 Fax	-

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.

3.27.5. Telemach

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.28.South Africa

3.28.1. [Nashua NCN](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.28.2. [Vodacom](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.

3.29.Spain

3.29.1. [LCR](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.29.2. [Telecable](#)

System	OSBiz
Supported since version	V2R1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.29.3. [vozelia](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	- / √
T.38 Fax	-

3.29.4. [VozTelecom](#)

System	OSBiz
Supported since version	V2_R2.0.0
Provider	
SIP DID account	√
SIP Client account	
Features	
CLIP / CLIR	√/√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√
Multisite	-

3.30.Sweden

3.30.1. [Tele2](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√ *1
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

*1 no registration / static IP is used

Note: Tele2 is released for SIP MEX feature (available only in OSBiz since V1R3)

3.30.2. [Telia](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	√ / -
T.38 Fax	√ *1

*1 = only outgoing

3.31.Switzerland

3.31.1. [E-fon AG](#)

System	OSBiz
Supported since version	V1_R3.3.553
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.31.2. [Improware](#)



System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	<i>not relevant in SWZ</i>
CLIP / CLIR	yes / yes
CLIP no Screening	yes ¹⁾
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes ²⁾
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

Remarks:

¹⁾ Clip no Screening needs to be booked at ITSP (one time fee)

²⁾ RFC2833 payload type MUST be set to 101 in the system

3.31.3. [Nexphone](#)

System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes ¹⁾
Codecs G711/G729	yes / yes
T.38 Fax	no ²⁾
Secure trunk	no

Remarks:

¹⁾ Nexphone does not support RFC2833 negotiation. RFC2833 payload type MUST be configured with 101 in the system and connected SIP devices

²⁾ T.38 MUST be deactivated in the system

3.31.4. [Peoplefone AG \(CH\)](#)

System	OSBiz
Supported since version	V2_R0.3.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.31.5. phonestar*



System	OpenScape Business
Released with Version	V3R4
Phonestar*	Features & Capabilities
Account (DID/Client)	<i>DID</i>
Multisite	<i>yes - dedicated trunk</i>
CLIP / CLIR	<i>yes</i>
CLIP no Screening	<i>yes</i>
COLP	<i>no</i>
Call Forwarding (302)	<i>no</i>
DTMF (RFC2833/4733)	<i>yes</i>
Codecs G.722/G.711/G729	<i>yes / yes / no</i>
T.38 Fax	<i>yes</i>
Secure trunk	<i>no</i>

Remarks:

- The use of the G.722 codec must be enabled on the end devices with priority 1 (first line codec). The use of G.722 depends on the properties of the remote station (end device, ITSP system connection, ...).
- CLIP no Screening is available in the default configuration.
- UC-Fax is not released for the **phonestar*** SIP-Trunk.

3.31.6. sipcall

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.

3.31.7. Sunrise

System	OSBiz
Released with Version	V1R3.3 update with V3R0.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes ¹⁾
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Sunrise

¹⁾ only Payload Type 101 is supported -> OSBiz and SIP endpoints must be configured accordingly

3.31.8. [Swisscom Enterprise SIP](#)

System	OpenScape Business
recertified for Version	V2R2 V3R4 (re-certified)
Features & Capabilities	
Account (DID/Client)	<i>DID</i>
Multisite	<i>yes</i>
CLIP / CLIR	<i>yes</i>
CLIP no Screening	<i>yes</i>
COLP	<i>yes</i>
Call Forwarding (302)	<i>yes</i>
DTMF (RFC2833/4733)	<i>yes ¹⁾</i>
Codecs G.711/G.729	<i>yes / yes</i>
T.38 Fax	<i>yes</i>
Secure trunk	<i>no</i>

¹⁾ Payload Type 101 is preferred -> System and SIP endpoints have to be configured accordingly

3.31.9. [Swisscom Smart Business Communication](#)

System	OpenScape Business
recertified for Version	V2R0 V3R3 (re-certified)
Features & Capabilities	
Account (DID/Client)	<i>DID</i>
Multisite	<i>no</i>
CLIP / CLIR	<i>yes</i>
CLIP no Screening	<i>yes</i>
COLP	<i>no</i>
Call Forwarding (302)	<i>yes</i>
DTMF (RFC2833/4733)	<i>yes ¹⁾</i>
Codecs G711/G729	<i>yes / yes</i>
T.38 Fax	<i>no</i>
Secure trunk	<i>no</i>

¹⁾ Payload Type 101 is preferred -> System and SIP endpoints have to be configured accordingly

3.31.10. [Swisscom Smart Business Connect Internet Trunk](#)

System	OpenScape Business
recertified for Version	V3R4
Features & Capabilities	
Account (DID/Client)	<i>DID</i>
Multisite	<i>no</i>
CLIP / CLIR	<i>yes</i>
CLIP no Screening	<i>yes</i>
COLP	<i>no</i>
Call Forwarding (302)	<i>yes</i>
DTMF (RFC2833/4733)	<i>yes ¹⁾</i>
Codecs G722/G711/G729	<i>yes / yes / no</i>
T.38 Fax	<i>no</i>
Secure trunk	<i>yes</i>

¹⁾ Payload Type 101 is preferred -> System and SIP endpoints have to be configured accordingly

3.31.11. [Telco Pack SA](#)

System	OSBiz
Supported since version	V1_R3.3
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.31.12. UPC CH Internet Registration



System	OSBiz
Released with Version	V2R7.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes ¹⁾
COLP	yes
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks:

¹⁾ need to be booked at UPC

Please check the configuration description for details about T.38 and DTMF configuration.

3.31.13. UPC CH Internet Static IP



System	OSBiz
Released with Version	V2R7.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes ¹⁾
COLP	yes
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks:

¹⁾ need to be booked at UPC

Please check the configuration description for details about Port, T.38 and DTMF configuration.

The formerly defined Cablecom profile is no longer available in OpenScape Business.

3.31.14. vtx

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.32. United Kingdom

3.32.1. [Broadcloud](#)

see [Broadcloud](#)

3.32.2. [BT IPVS](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

BT IPVS is available for existing installations. The profile should not be used for new installations

3.32.3. BT Wholesale SIP Trunking



System	OSBiz
Released with Version	V2R4.1
ITSP Features & Capabilities	
Account (DID/Client)	DID ¹⁾
Multisite	yes ²⁾
CLIP / CLIR	yes / yes
CLIP no Screening	yes ³⁾
COLP	-
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes ⁴⁾
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Remarks:

¹⁾ No registration is used

A static IP is a prerequisite to connect to the BT Wholesale SIP Trunking service. Please see the configuration description for details.

²⁾ the service can provide multiple unrelated number ranges on the same trunk

³⁾ CLIP no Screening is supported if the number is pre-approved by BT but not in call diversion scenarios.

⁴⁾ Currently the service doesn't ensure that all DTMF sent as RTP events, meaning another SIP customer may send you in-band tones only. However, later this year BT will be adding in the functionality for DTMF destined for a customer to be RTP events only.

3.32.4. [BT Wholesale Hosted Communications](#)



System	OSBiz
Released with Version	V4.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	no
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Remarks:

There is a suite of features provided at a trunk level which can be used to introduce additional functionality to the ITSP, however, there are limitations on which features are and are not supported with OpenScape Business. Please check the configuration document for details

3.32.5. [Gamma](#)



System	OSBiz
Released with Version	V2R7.1 (update)
ITSP Features & Capabilities	
Account (DID/Client)	DID ¹⁾
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes ²⁾
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Remarks:

¹⁾ No registration is used

²⁾ optional feature, needs to be booked at Gamma CLIP no Screening (known to Gamma as CLI Flexibility) is supported if the number is pre-approved by Gamma but not in call diversion scenarios.

Customer specific profile entries are needed for proxy address

A static IP is a prerequisite to connect to Gamma.

For security reasons OpenScape Business uses dedicated SIP server ports for internal (5060) and external (5070) traffic. Gamma handle SIP traffic on port 5060 in default, thus the external SIP port in Openscape Business MUST be configured to 5060.

3.32.6. [KCOM](#)

System	OSBiz
Supported since version	V2_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.32.7. [TalkTalk](#)

System	OSBiz
Supported since version	V2_R0.3.11 24
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.32.8. [tIPicall](#)

System	OSBiz
Supported since version	V1_R3.2
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

tIPicall is available for existing installations. The profile should not be used for new installations

3.32.9. Vodafone



System	OSBiz
Released with version	V2R3
Capabilities&Features	
Account (DID/Client)	DID ¹⁾
Multisite	yes ²⁾
CLIP / CLIR	yes / yes
COLP	-
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes

Remarks:

¹⁾ No registration is used

²⁾ Multisite is supported by ITSP (numbers from different location areas are possible)

3.32.10. VoiceFlex

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.32.11. VoIP Ltd i-Line

System	OSBiz
Supported since version	V1_R3.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	-
COLP	-
DTMF (RFC 2833)	√ / -
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.33.U.S.A.

3.33.1. [AT&T](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.33.2. [Broadcloud](#)

see [Broadcloud](#)

3.33.3. [CenturyLink](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√ *1)
SIP Client account	-
Features	
CLIP / CLIR	√ / √
COLP	√
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / -
T.38 Fax	√

*1) CenturyLink will use customer specific server addresses, thus the profile needs to be completed during configuration of the system

3.33.4. [Fusion 360](#)



System	OSBiz
Released with Version	V2R3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes ¹⁾
CLIP / CLIR	yes / yes
COLP	-
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes ²⁾
T.38 Fax	no

Remarks:

¹⁾ Multisite is supported by ITSP (under the same registration, numbers from different location areas are possible)

²⁾ G729A is possible, but not recommended. G729AB is not supported

Please note that our tests have shown that fax transmission using the T.38 protocol with the Fusion 360 trunks was not successful. T.38 MUST be deactivated in the system.

3.33.5. [IPfone](#)



System	OSBiz
Released with Version	V2R7.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	no
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no ¹⁾
Secure trunk	no

Remarks:

¹⁾ T.38 must be disabled in system

3.33.6. [Intermedia.net Inc](#)

System	OSBiz
Supported since version	V2_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

3.33.7. [SoTel](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

3.33.8. [Windstream](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	-

Remarks:

Only the actual Broadsoft Platform is tested and released.

Manual entries are needed for the Basic servers (Proxy-Registrar) depending on platform and region.

3.33.9. [XO](#)

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	√
Features	
CLIP / CLIR	√
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	√ / √
T.38 Fax	√

Table of History

Version	Date	Changes
...
88	2020-06-02	<p>Update for V3:</p> <p>Add new ITSP profiles:</p> <ul style="list-style-type: none"> Unitymedia – Germany CITEC Universe SIP Trunk – Germany Omnidat – Germany R-Kom – Germany ImproWare - Switzerland BCOM – Belgium X2Com – Belgium WOBCOM – Germany Wilhelm.tel – Germany Codepi – France Datel – Germany Tele AG – Germany Nexphone - Switzerland <p>Update supported ITSP profiles:</p> <ul style="list-style-type: none"> Destiny (use session timer) BKM – Belgium (server names, call number format,...) Telekom company Flex – original number in From Telekom DLAN SIP Trunk – original number in From <p>Delete obsolete profiles:</p> <ul style="list-style-type: none"> Acropolis – France Tus Telekom
89	2020-10-19	<p>Update for V3R0.1:</p> <p>Add new ITSP profiles:</p> <ul style="list-style-type: none"> TelemaxX – Germany VoipQ - Netherlands <p>Update supported ITSP profiles:</p> <ul style="list-style-type: none"> Sunrise – Switzerland (general update) <p>Delete obsolete profiles:</p> <p>n/a</p>
90	2021-03-01	<p>Update for V3R1:</p> <p>Add new ITSP profiles:</p> <ul style="list-style-type: none"> Voiceworks DE – Germany <p>Update supported ITSP profiles:</p> <ul style="list-style-type: none"> Voiceworks NL – Netherlands (new name) <p>Delete obsolete profiles:</p> <p>n/a</p>

Version	Date	Changes
91	2021-12-13	<p>Update for V3R1.2:</p> <p>Add new ITSP profiles:</p> <ul style="list-style-type: none"> KPN TLS NL – Netherlands Pocos NL - Netherlands rgi VoIP Trunk 200 – Germany Scaldis B.V. - Netherlands <p>Update supported ITSP profiles:</p> <ul style="list-style-type: none"> Ecotel sip Trunk 2.0 – support of Geo-Redundancy purtel – stopped T.38 Fax service Telekom Company Flex – no switch back to the primary SIP outbound proxy within 15 minutes (hidden parameter – automatically active) Telekom DLAN SIP Trunk – no switch back to the primary SIP outbound proxy within 15 minutes (hidden parameter – automatically active) <p>Obsolete profiles (to be deleted in upcoming HotFix):</p> <ul style="list-style-type: none"> KPN TLS NDL – Netherlands Pocos NDL - Netherlands
92	2022-06-01	<p>Update for V3R2:</p> <p>Add new ITSP profiles:</p> <ul style="list-style-type: none"> AAPT – Australia <p>Released without profiles:</p> <ul style="list-style-type: none"> EasyFone - Germany Keyyo – France <p>Update supported ITSP profiles:</p> <ul style="list-style-type: none"> Vodafone Anlagenanschluss R4 – recertified R4.b incl. TLS (w/o profile change) <p>Delete obsolete profiles:</p> <ul style="list-style-type: none"> KPN TLS NDL – Netherlands Pocos NDL - Netherlands
93	2022-06-08	<p>2nd Update for V3R2:</p> <p>Released without profiles:</p> <ul style="list-style-type: none"> envia TEL - Germany
94	2022-12-01	<p>Update for V3R2.1:</p> <p>Add new ITSP profiles:</p> <ul style="list-style-type: none"> Sparks Voice Connect – Australia Orange BE SIP – Belgium Keyyo - France EasyFone – Germany envia TEL – Germany G9 Telecom - Portugal <p>Released without profiles:</p> <ul style="list-style-type: none"> n/a <p>Update supported ITSP profiles:</p> <ul style="list-style-type: none"> Orange BE S&F - Belgium KPN TLS NL – Netherlands Vodafone Anlagenanschluss R4 – Germany Sunrise - Switzerland <p>Delete obsolete profiles:</p> <ul style="list-style-type: none"> Orcon Ltd – Australia TelstraClear WSIP - Australia

Version	Date	Changes
95	2023-10-06	<p>Update for V3R3:</p> <p>Add new ITSP profiles:</p> <ul style="list-style-type: none"> Drei Business SIP Connect – Austria Dstny – France Komro – Germany Magenta – Austria RoutIT TLS- Netherlands Vodafone Anlagenanschluss R5 – Germany <p>Released without profiles:</p> <ul style="list-style-type: none"> Helinet - Germany htp Business Flex Smart – Germany <p>Update supported ITSP profiles:</p> <ul style="list-style-type: none"> BT Wholesale – UK Telekom Company Flex - Germany <p>Delete obsolete profiles:</p> <ul style="list-style-type: none"> ecotel sipTrunk Connect 1.0 – Germany ecotel sipTrunk DDI – Germany Tele 2 – Austria UPC Austria – Austria Vodafone Anlagenanschluss – Germany Vodafone Anlagenanschluss R3 – Germany
96	2023-12-11	<p>2nd Update for V3R3:</p> <p>Released without profiles:</p> <ul style="list-style-type: none"> BITel Business SIP Flex- Germany Gamma NGN (DE) – Germany wittenberg-net GmbH - Germany <p>Update supported ITSP without profile change:</p> <ul style="list-style-type: none"> EWE Voice+ SIP Trunk Flex – Germany
97	2024-03-11	<p>Update for V3R3.1:</p> <p>Add new ITSP profiles:</p> <ul style="list-style-type: none"> BITel Business SIP Flex - Germany Gamma NGN (DE) – Germany Helinet – Germany htp Business Flex SIP-Trunk smart – Germany wittenberg-net GmbH – Germany <p>Released without profiles:</p> <ul style="list-style-type: none"> Net4You-Voice4Biz - Austria <p>Update supported ITSP profiles:</p> <ul style="list-style-type: none"> easybell – Germany (CLIR) EWE Voice+ SIP Trunk – Germany (Domain, CLIR, CNS) <p>Update supported ITSP without profile change:</p> <ul style="list-style-type: none"> M-net Premium SIP-Trunk – Germany (CNS) Universe SIP Connect – Germany (TLS, CNS) <p>Delete obsolete profiles:</p> <ul style="list-style-type: none"> n/a

Version	Date	Changes
98	2024-07-05	<p>Update for V3R3.2:</p> <p>Add new ITSP profiles:</p> <p> Net4You-Voice4Biz - Austria</p> <p>Update ITSP profiles:</p> <p> EWE Voice+ SIP Trunk – Germany (TLS)</p> <p> M-net Premium SIP-Trunk – Germany (CNS)</p> <p> Universe SIP Connect – Germany (TLS, CNS)</p> <p>Update ITSP without profile change:</p> <p> M-net Premium SIP-Trunk – Germany (media renegotiation)</p> <p> Swisscom Smart Business Communication (new config guide)</p> <p>Delete obsolete profiles:</p> <p> HFO Telecom NGN - Germany</p> <p> Skype for Business – all countries</p> <p> Swisscom BCON - Switzerland</p> <p> Swisscom VoipGate - Switzerland</p>
99	2024-12-03	<p>Update for V3R4:</p> <p>From now on new certifications are released for</p> <p>OpenScape Business V3 Mainboard Familiy</p> <p>OpenScape Business S</p> <p>Add new ITSP profiles:</p> <p> herweck callamar – Germany</p> <p> Virtual Call – Austria, Brazil, Germany, Spain, Switzerland, UK</p> <p>Beta without profiles:</p> <p> Vodafone Anlagenanschluss R6 – Germany</p> <p>Update ITSP profiles:</p> <p> M-net Premium SIP-Trunk – Germany (media renegotiation)</p> <p>Update ITSP without profile change:</p> <p> Swisscom Enterprise SIP - Switzerland</p> <p>Delete obsolete profiles:</p> <p> n/a</p>
100	2025-02-12	<p>Update for V3R4:</p> <p>Released without profiles:</p> <p> Kwebbl SIP Trunk – International</p> <p> phonestar* - Switzerland</p>
101	2025-04-09	<p>Update for V3R4:</p> <p>Released without profiles:</p> <p> Swisscom Smart Business Connect Internet Trunk – Switzerland</p>
102	2025-05-15	<p>Update for V3R4.1:</p> <p>Released ITSP profiles:</p> <p> Proximus Enterprise Voice - Belgium</p> <p> Vodafone Anlagenanschluss R6 (TCP) – Germany</p> <p>Released without profiles:</p> <p> GVG Glasfaser, Thüringer Netkom – Germany</p>

The information conveyed in this document is confidential and proprietary to Mitel® and is intended solely for Mitel employees and members of Mitel's reseller channel who specifically have a need to know this information. If you are not a Mitel employee or a Mitel authorized PARTNER, you are not the intended recipient of this information. Please delete or return any related material. Mitel will enforce its right to protect its confidential and proprietary information and failure to comply with the foregoing may result in legal action against you or your company.