Overview about released SIP Providers





Table of Contents

1.	Introduction	8
2.	Definition of Features between OpenScape Business and SIP Provider	9
3.	ITSP Details	10
3.1.	International	10
3.1.1.	Broadcloud Germany - France - Italy - UK - Australia – USA	10
3.1.2.	COLT international	11
3.1.3.	Skype connect international	11
3.1.4.	Verizon international	11
3.2.	Australia	12
3.2.1.	AAPT SIP Connect	12
3.2.2.	Broadcloud	12
3.2.3.	Commander Primus	12
3.2.4.	engin	13
3.2.5.	Internode	13
3.2.6.	Spark Voice Connect SIP	13
3.3.	Austria	14
3.3.1.	A1 SIPtrunk - registrierend	14
3.3.2.	Drei Business SIP Connect	15
3.3.3.	Magenta Business Voice SIP	16
3.3.4.	Kabelplus Business Phone	16
3.3.5.	IP-Austria	17
3.3.6.	LinzAG City Voice	17
3.3.7.	Neotel	17
3.3.8.	Peoplefone AG	18
3.3.9.	SalzburgAG CableLink	18
3.4.	Belgium	19
3.4.1.	Belgacom.IMS / Proximus	19
3.4.2.	BCOM	19
3.4.3.	Destiny	19
3.4.4.	BKM	20
3.4.5.	gnTel	20
3.4.6.	IPnexia – Belgium - Luxemburg	21
3.4.7. 3.4.8.	ORANGE Telenet	22 24
3.4.8.	WIN	24
3.4.10		24
3.5.	Brazil	25
3.5.1.	vivo	25
3.5.2.	Voitel	25
3.6.	Canada	26
3.6.1.	BabyTEL	26
3.7.	Chile	26
3.7.1.	ENTEL NGN	26
3.8.	Czech Republic	27
3.8.1.	GTS	27
3.8.2.	O2 CZ	27
3.8.3.	T-mobile	27

3.9.	Denmark	28
3.9.1.	Global Connect	28
3.9.2.	TDC DK	28
3.9.3.	Telia	29
3.9.4.		29
3.10.	Finland	30
3.10.1		30
	2. Länsilinkki	30
3.10.3		30
3.10.4		31
3.11.	Estonia	31
3.11.1		31
3.12.	France	32
3.12.1	• •	32
3.12.2		32
3.12.3	1	32
3.12.4	1	33
3.12.5	•	34
3.12.6	<u> </u>	35
3.12.7		35
3.12.8		36
3.12.9		36
3.12.1	<u>e</u>	37
	1. Keyyo	37
3.12.1	•	38
3.12.1	•	39
3.12.1		39
	5. Paritel Operateur	40
3.12.1	6. Sewan Communications	40
3.13.	Germany	41
3.13.1		41
3.13.2	2. 1&1 Versatel	41
3.13.3	1	42
3.13.4	l. Broadcloud	42
3.13.5	5. BITel	43
3.13.6	6. CITEC Universe SIP Trunk	44
3.13.7		45
3.13.8	3. Deutsche Telefon	46
3.13.9	easybell	47
3.13.1	0. EasyFone	48
3.13.1	1. ecotel sipTrunk 2.0	49
3.13.1	2. ennit	50
3.13.1	3. envia TEL	50
3.13.1	4. equada	50
3.13.1	5. ewe	51
3.13.1	6. Gamma	52
3.13.1	7. gmx	52
3.13.1	8. gnTel	53
3.13.1	9. Helinet	53
3.13.2	20. HFO - Germany	54
3.13.2	21. HL komm	54

3.13.22	. htp	55
3.13.23	. Inexio	56
3.13.24	. komroVoIP-Trunk	57
3.13.25	. M-Net Premium	58
3.13.26	. MK Netzdienste	59
3.13.27	. NetCologne ProPhone SIP	60
3.13.28	. NetCom BW	61
3.13.29	. NFON	62
3.13.30	. O2 All-IP Voice SIP	63
3.13.31	. omnidat	64
3.13.32	. Peoplefone AG (DE)	64
	. PhoneVoice	65
	. purtel	65
	. Plusnet IPfonie Extended	66
	. Plusnet IPfonie Extended Connect	66
	. reventix	67
	. rgi VoIP Trunk 200	67
	. R-Kom	68
3.13.40	10	68
3.13.41	. Steffel-Voice	69
3.13.42	. Tele AG	70
3.13.43	. TeleData	71
3.13.44	± •	72
3.13.45	. Telekom IP-As mit MSN	73
	. Telekom DeutschlandLAN SIP-Trunk Registered Mode	74
	. TelemaxX	75
3.13.48	7	76
3.13.49		77
3.13.50		78
3.13.51	•	78
	. Unitymedia	79
	. Vodafone Anlagenanschluss R4	80
3.13.54		81
3.13.55		82
	witherm.tel	83
	wittenberg-net GmbH	84
	. WOBCOM	85
	Greece	86
3.14.1.	COSMOTE	86
	Hungary	87
3.15.1.	Netfone Telecom	87
3.16. I	Hong Kong	88
3.16.1.	Hong Kong Broadband Network	88
3.16.2.	HGC	89
3.17. I	taly	90
3.17.1.	Broadcloud	90
3.17.2.		90
3.17.3.	TWT	90
3.17.4.	Viatek	91
3.18. I	Lichtenstein	91

3.18.1. FL1 Telecom	91
3.19. Luxembourg	91
3.19.1. IPnexia	91
3.20. Mexico	92
3.20.1. Telefonica	92
3.21. Netherlands	93
3.21.1. BCOM	93
3.21.2. BLU Networks	93
3.21.3. Deanconnect B.V.	94
3.21.4. gnTel	94
3.21.5. infopact	95
3.21.6. KPN VoiPConnect,	95
3.21.7. KPN TLS NL (KPN EEN over TLS)	95
3.21.8. Motto Communications	96
3.21.9. OneCentral	96
3.21.10. OneXS	96
3.21.11. Pocos	97
3.21.12. RoutIT	97
3.21.13. RoutIT TLS	98
3.21.14. Scaldis B.V.	98
3.21.15. SIGNET B.V	99
3.21.16. Speakup 3.21.17. tele2	100 100
3.21.17. tele2 3.21.18. T-Mobile	100
3.21.19. Vodafone	100
3.21.20. Voiceworks NL	101
3.21.21. Voiceworks MEX	102
3.21.22. VoipQ	102
3.21.23. VoIPXS	103
3.21.24. X2COM	103
3.21.25. Ziggo	104
3.21.26. Vodafone Ziggo	104
3.22. New Zealand	105
3.22.1. Orcon Ltd	105
3.22.2. TelstraClear	105
3.22.3. voyager	106
3.23. Portugal	107
3.23.1. Altice (Portugal Telecom)	107
3.23.2. G9 Telecom	107
3.23.3. Portugal Telecom	108
3.23.4. Vodafone	108
3.24. Saudi Arabia	109
3.24.1. Saudi Telecom Company	109
3.25. Serbia	110
3.25.1. Orion Telekom	110
3.25.2. Telenor	110
3.26. Slovakia	111
3.26.1. Slovak Telekom	111
3.27. Slovenia	111
3.27.1. A1 SIP Trunk	111

3.27.2.	Detel	111
3.27.3.	MegaM	112
3.27.4.	T-2	112
3.27.5.	Telemach	112
3.28. So	outh Africa	113
3.28.1.	Nashua NCN	113
3.28.2.	Vodacom	113
3.29. St	pain	114
3.29.1.	LCR	114
3.29.2.	Telecable	114
3.29.3.	vozelia	114
3.29.4.	VozTelecom	115
3.30. Sv	weden	116
3.30.1.	Tele2	116
3.30.2.	Telia	116
3.31. Sv	witzerland	117
3.31.1.	E-fon AG	117
3.31.2.	Improware	117
3.31.3.	Nexphone	118
3.31.4.	Peoplefone AG (CH)	118
3.31.5.	sipcall	119
3.31.6.	Sunrise	120
3.31.7.	Swisscom BCON	121
3.31.8.	Swisscom Enterprise SIP	121
3.31.9.	Swisscom Smart Business Communication	122
3.31.10.	1	122
3.31.11.		122
3.31.12.	<u> </u>	123
	UPC CH Internet Static IP	124
3.31.14.	vtx	124
	nited Kingdom	125
3.32.1.	Broadcloud	125
3.32.2.	BT IPVS	125
3.32.3.	BT Wholesale SIP Trunking	126
3.32.4.	BT Wholesale Hosted Communications	127
3.32.5.	Gamma	128
3.32.6.	KCOM	128
3.32.7.	TalkTalk	129
3.32.8.	tIPicall	129
3.32.9.	Vodafone VoiceFlex	130
3.32.10. 3.32.11.	VoIP Ltd i-Line	130 130
	.S.A.	131
3.33.1.	AT&T	131
3.33.2. 3.33.3.	Broadcloud Century Link	131 131
3.33.4.	CenturyLink Fusion 360	131
3.33.5.	IPfone	132
3.33.6.	Intermedia.net Inc	132
3.33.7.	SoTel	134

Table of F	listory	135
3.33.9.	XO	134
3.33.8.	Windstream	134

1. Introduction

The tables below provide an overview of tested ITSP providers for OpenScape Business.

It has to be emphasized that the documented features represent the result when the test was finished.

Important Note:

It is highly recommended to check for the most current SW on SW-Download Server within the Unify Partner Portal.

For more information: osbiz-certification@atos.net

Definition of Features betweenOpenScape Business and SIP Provider

SIP DID Account

Provider supplies the customer with a range of call numbers for direct inward dialing, accessible with one or no SIP registration.

SIP Client Account

Provider supplies the customer with one or more single call numbers which are registered separately.

Multisite

Provider allows handling of numbers from different locations/areas via a single trunk or dedicated trunks for each location/area. For more info if each location/area needs a dedicated registration please check https://wiki.unify.com/images/7/1/MultiRegistrationForITSP.pdf.

CLIP no Screening

Provider allows sending of calling party numbers different from the numbers assigned to the account (e.g. toll-free numbers 0800-, or original calling party number in case of call forwarding).

CLIP/CLIR

Calling line indication presentation / calling line indication restriction. Call numbers are displayed or suppressed in ringing state.

COLP

Connected line presentation / connected line restriction. Connected call numbers are displayed or suppressed in connected state.

Call Forwarding (302)

Provider support call forwarding (also referred as call deflection) initiated with a 302 response.

DTMF

Transmission of dual tone multi frequency signaling is used e.g. for voicemail or conference server access. RFC 2833 support is needed to control e.g. UC-Suite.

Codecs

G.711: 64 kbps coding, variants a-law and u-law

G.729: 8 Kbps coding, variants A and AB with silence insertion

For IP-IP calls other codecs (like G.722) can be negotiated between the endpoints. Negotiation of such codecs is supported by the OpenScape system

FAX

T.38 protocol allows safe transmission also for multi-page documents.

G.711 is not recommended.

Secure Trunk

Provider offers a secured SIP trunk (TLS transport and SRTP media).



3. ITSP Details

3.1. International

3.1.1. Broadcloud Germany - France - Italy - UK - Australia – USA



System	OSBiz		
Released with Version	V2R3		
ITSP Features & Capabilities			
Account (DID/Client)	DID		
Multisite	ITSP support multiple call numbers from different areas in the same country on the same trunk		
CLIP / CLIR	yes / yes		
CLIP no Screening	no		
COLP	-		
DTMF (RFC2833/4733)	yes		
Codecs G711/G729	yes / yes		
T.38 Fax	yes		

Remarks:

In a transit call forwarding scenario Broadcloud provides the number of the originating caller. E.g. external A calls internal B. B is forwarded to external C. C get the number information of A

During setup of the ITSP trunk in OpenScape Business the country specific server addresses needs to be configured in the Broadcloud profile.



3.1.2. **COLT** international

System	OsBiz
Supported since version	V1_R1.1.0
Provider(profiles see *1)	
SIP DID account	√ * 2
SIP Client account	-
Features	
CLIP / CLIR	V
COLP	-
DTMF (RFC 2833)	V
Codecs G.711/G.729	V / V
T.38 Fax	V

- *1 = COLT VPN Access may need additional manual configuration) COLT UK & Europe
- = no registration *2

3.1.3. **Skype connect** international

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	V
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-

3.1.4. **Verizon** international

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	



3.2. Australia

3.2.1. AAPT SIP Connect

♠AAPT [BusinessConnect]

System	OSBiz	
Released with Version	V3R2	
ITSP Features & Capab	ilities	
Account (DID/Client)	DID	
Multisite	yes - single trunk	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	no	
Secure trunk	no	

3.2.2. <u>Broadcloud</u>

see Broadcloud Germany - France - Italy - UK - Australia - USA

3.2.3. <u>Commander Primus</u>

System	OsBiz
Supported since version	V1_R3.1
Provider	
SIP DID account	\checkmark
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-(P)
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V



3.2.4. **engin**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	$\sqrt{}$
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V

3.2.5. <u>Internode</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	$\sqrt{}$
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V

3.2.6. Spark Voice Connect SIP

System	OpenScape Business	
Released with Version	V3R2.1	
ITSP Features & Capab	ilities	
Account (DID/Client)	DID	
Multisite	yes - single trunk	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	yes	
Secure trunk	no	




Issue 96



3.3. Austria

3.3.1. A1 SIPtrunk - registrierend





Remarks:

Secure trunk

A1 delivers a "A1 Router" to the customer which is used to terminate the SIP trunk.

no

¹⁾ Clip no Screnning needs to be activated by A1.



3.3.2. **Drei Business SIP Connect**

System	OpenScape Business	
Released with Version	V3R3	
Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes - single trunk / dedicated trunk	
CLIP / CLIR	yes	
CLIP no Screening	yes 1)	
COLP	yes	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	no	
Secure trunk	no	



Remarks:

CLIP no Screening can be booked optional
 UC-Fax is not released for *Drei Business SIP Connect*



3.3.3. <u>Magenta Business Voice SIP</u>

System	OpenScape Business	
Released with Version	V3R3	
	Features & Capabilities	
Account (DID/Client)	DID/MSN	
Multisite	yes - single trunk	
CLIP / CLIR	yes	
CLIP no Screening	yes - if ordered	
COLP	yes	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	yes	
Secure trunk	no	



Remarks:

SIP External must be changed to 5060. It is recommended to set the SIP port (internal) to 5070.

3.3.4. Kabelplus Business Phone

System	OsBiz
Supported since version	V2_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	ı
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V



Overview about released SIP Providers



3.3.5. **IP-Austria**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	√ 1)
Codecs G.711/G.729	√/-
T.38 Fax	2)

¹⁾ Only Payload Type 101 supported -> System and SIP endpoints has to be configured accordingly

Service call 0900 generally not allowed with IPAustria

3.3.6. **LinzAG City Voice**

System	OsBiz
Supported since version	V2_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	$\sqrt{}$

3.3.7. **Neotel**

System	OsBiz
Supported since version	V2_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	$\sqrt{}$

²⁾ Only T.38 outbound supported. LX was tested with OSO-fax-server. FAX with G.711 only working properly with 10ms frame size



3.3.8. Peoplefone AG

System	OsBiz
Supported since version	V2R6
Provider	
SIP DID account	
SIP Client account	-
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	V/V
T.38 Fax	-

SalzburgAG CableLink 3.3.9.

System	OsBiz
Supported since version	V2_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	



3.4. Belgium

3.4.1. <u>Belgacom.IMS / Proximus</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√ *1
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-

^{*1 =} no SIP registration UC-Suite is not yet released for Belgacom IMS

3.4.2. **BCOM**

for details on BCOM see the table BCOM

3.4.3. **Destiny**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	
SIP Client account	
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	√
Codecs G.711/G.729	V/V
T.38 Fax	



3.4.4. **BKM**

Formerly named Hexacom



System	OSBiz
Released with Version	V3
ITSP Features & Capab	ilities
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

Remarks:

With V3 a major update of the BKM profile is available.

BKM offers two types of trunks:

- 1. accessible via public network: for this type of trunk the profile could be used without changes
- 2. access via private link: for this type of access the settings need to be adapted, please check the configuration document

3.4.5. **gnTel**

for details on gnTel see the table gnTel





3.4.6. <u>IPnexia</u> – Belgium - Luxemburg

System	OSBiz		
Released with Version	V2R6.2		
ITSP Features & Capab	es & Capabilities		
Account (DID/Client)	DID		
Multisite	no		
CLIP / CLIR	yes / yes		
CLIP no Screening	yes		
COLP	no		
Call Forwarding (302)	yes		
DTMF (RFC2833/4733)	yes		
Codecs G711/G729	yes / yes		
T.38 Fax	no		
Secure trunk	no		





3.4.7. **ORANGE**

System	OSBiz	
Released with Version	V2R3.1 update: V3R2.1	
profile	Orange BE S&F	
ITSP Features & Capabi	bilities	
Account (DID/Client)	DID	
Multisite	yes - dedicated trunks	
CLIP / CLIR	yes / yes	
COLP	no	
CLIP no Screening	yes 1)	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	yes	

1.30 Fax	yes	
System	OSBiz	
Released with Version	V3R2.1	
profile	Orange BE SIP	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes - dedicated trunks	
CLIP / CLIR	yes / yes	
COLP	no	
CLIP no Screening	yes 1)	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	ves	

Remarks:

The registrar/proxy IP address will be different for each customer

Orange delivers a CPE device to the customer. This CPE device has typical an xDSL uplink to the providers SIP Trunk. The CPE does get an IP Address which is in the same subnet of the customer PBX. ITSP is reached via static route configured in OSBIZ. Please check the configuration guide. ISP is reached via different router.





¹⁾ In default the Orange profile has CLIP no Screening activated. The user must sign an agreement for CLIP no Screening. As long as the user has not signed the agreement with Orange, forwarded calls will be rejected! If CLIP no Screening agreement is not signed the profile needs to be changed manually.



3.4.8. <u>Telenet</u>

System	OSBiz	
Released with Version	V1R1	
ITSP Features & Capab	ilities	
Account (DID/Client)	DID	
Multisite		
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	yes	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	yes	
Secure trunk	no	



Remarks:

Customer specific profile entries are needed for domain name and Proxy.

3.4.9. <u>WIN</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√ *1)
SIP Client account	ı
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-

*1) = no registration

UC-Suite is not yet released

Overview about released SIP Providers

3.4.10. **X2COM**

for details on X2COM see the table X2COM



3.5. Brazil

3.5.1. *vivo*



System	OSBiz	
Released with Version	V2R7.1	
ITSP Features & Capab	ilities	
Account (DID/Client)	DID	
Multisite	-	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	no	
Secure trunk	no	

Remarks:

Vivo provide 4 different link types.

Please check the configuration document about the necessary configuration steps: Link 1,2 and 4 Customer specific profile entries are needed for domain and proxy. Link 4: Customer specific profile entries are needed for domain, proxy and **inbound proxies**. Static routes must be configured.

3.5.2. <u>Voitel</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	√/-
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V



3.6. Canada

3.6.1. **BabyTEL**

System	OsBiz
Supported since version	V2_R0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V

3.7. Chile

3.7.1. **ENTEL NGN**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.



3.8. Czech Republic

3.8.1. <u>GTS</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	$\sqrt{}$

3.8.2. <u>02 CZ</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V

3.8.3. **T-mobile**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	



3.9. Denmark

3.9.1. Global Connect

System	OsBiz
Supported since version	V1_R3.3
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V

3.9.2. **TDC DK**

System	OsBiz
Supported since version	V2 R2.1.0_262
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	√/-
COLP	$\sqrt{}$
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V
Multisite	-)*

^{*)} Not supported by country



3.9.3. <u>Telia</u>



System	OSBiz
Released with Version	V2R2.2.0_279
ITSP Features & Capabilities	
Account (DID/Client)	DID 1)
Multisite	-
CLIP / CLIR	yes / yes
COLP	-
DTMF (RFC2833/4733)	yes ²⁾
Codecs G711/G729	yes / -
T.38 Fax	- 3)

Remarks:

3.9.4. **Uni-tel A/S**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	
SIP Client account	-
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	√/-
T.38 Fax	

¹⁾ No registration is used, Port 5060 MUST be used for SIP traffic

²⁾ Only Payload Type 101 supported -> System and SIP endpoints has to be configured accordingly

³⁾ T.38 is not supported in default, it can be requested if needed



3.10.Finland

3.10.1. *Elisa*

Certification was renewed with new platform of Elisa (Elisa NGN) in January 2013.

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	√/-
T.38 Fax	

3.10.2. Länsilinkki

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	$\sqrt{}$
DTMF (RFC 2833)	
Codecs G.711/G.729	√/-
T.38 Fax	V

3.10.3. <u>TDC</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√*1
SIP Client account	-
Features	
CLIP / CLIR	
COLP	$\sqrt{}$
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	V/V
T.38 Fax	$\sqrt{}$

^{*1):} no registration




3.10.4. <u>TeliaSonera</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	$\sqrt{}$
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V

3.11.Estonia

3.11.1. <u>Telia</u>





Remarks

Due to a problem with certain call scenarios a DSP board is needed to terminate the payload. See the configuration document for details.

Fax is not fully tested and not released



3.12.France

3.12.1. **Bouygues**

System	OsBiz
Supported since version	V2_R1.0.0
Provider	
SIP DID account	\checkmark
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{/}$
COLP	-
DTMF (RFC 2833)	√ 1)
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	$\sqrt{}$

¹⁾ Only Payload Type 101 supported -> System and SIP endpoints has to be configured accordingly

3.12.2. <u>Broadcloud</u>

see Broadcloud Germany - France - Italy - UK - Australia - USA

3.12.3. <u>codepi</u>

Custom	OCD:-
System	OSBiz
Released with Version	V3
ITSP Features & Capab	ilities
Account (DID/Client)	DID
Multisite	yes, single registration
CLIP / CLIR	yes / yes
CLIP no Screening	yes 1)
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no



Remarks:

Issue 96

¹⁾ Clip no Screening needs to be boocked at CODEPI



3.12.4. **Completel**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	V
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	



3.12.5. **Dstny**

System	OpenScape Business
Released with Version	V3R3
Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes – single and dedicated trunk
CLIP / CLIR	yes / no
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no





3.12.6. Foliateam Opérateur



System	OSBiz	
Released with Version	V2R7.1	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	yes	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	no	
Secure trunk	no	

Remarks:

T.38 MUST be deactivated in the OpenScape Business system

3.12.7. **Hexatel**

System	OsBiz
Supported since version	V1_R3.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	-
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	

Issue 96



3.12.8. *IP Directions*

System	OSBiz	
Released with Version	V2R7	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	no	
Secure trunk	no	



Remarks:

T.38 MUST be deactivated in the OpenScape Business system
Due to interoperability issues UC-Fax is not released with IP-Directions

3.12.9. *IPnexia*

for details on IPnexia see the table IPnexia Belgium



Issue 96



3.12.10. <u>Jaguar</u>



System	OSBiz
Released with Version	V2R7.1
ITSP Features & Capab	ilities
Account (DID/Client)	DID 1)
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	not supported 2)
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Remarks:

3.12.11. <u>Keyyo</u>

System	OSBiz
Released with Version	V3R2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes / yes
CLIP no Screening	no
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no



¹⁾ Special configuration of primary and secondary server needed, see configuration document for details.

²⁾ Jaguar requires a special signalling for Clip no Screnning which is not supported by OpenScape business



3.12.12. **MyStream**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	V
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-



3.12.13. **OpenIP**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	√/-
T.38 Fax	-

3.12.14. Orange Business Services SIP trunking

System	OSBiz
Released with Version	V2R4.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
COLP	no
CLIP no Screening	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / partly
T.38 Fax	yes
Secure trunk	no



Remarks:


To comply with the requirements of the Orange Business Services SIP trunk a special setup of OpenScape Business is needed. Please read the configuration description available in the Wiki. Customer specific profile entries are needed for domain name and proxy address

Special configuration is needed for the following parameters:

- EXT_SIP_PORT **MUST** be configured with 5060 (default is 5070)
- RFC 2833 payload type MUST be 101
- RFC 2198 support MUST be disabled
- G.729AB is NOT supported by ORANGE and **SHOULD** be disabled



3.12.15. Paritel Operateur





3.12.16. **Sewan Communications**

System	OsBiz
Supported since version	V1_R3.3.0
Provider	
SIP DID account	
SIP Client account	
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	



3.13.Germany

3.13.1. <u>1&1</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	$\sqrt{}$
T.38 Fax	-

3.13.2. 1&1 Versatel

System	OSBiz
Released with Version	V2R4.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
COLP	-
CLIP no Screening	yes 1)
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes ²⁾
secure trunk	no



Remarks:

¹⁾ CLIP no screening needs to be configured on the 1&1 Versatel platform

²⁾ UC-Fax is not released with 1&1 VersateI (This needs an enhancement in OpenScape Business and will be released in an upcoming version)



3.13.3. <u>autphone</u>



System	OSBiz
Released with Version	V2R7
ITSP Features & Capab	ilities
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes 1)
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Remarks:

3.13.4. **Broadcloud**

see Broadcloud Germany - France - Italy - UK - Australia - USA

¹⁾ CLIP no Screening needs to be booked at ITSP



3.13.5. <u>BITel</u>

System	OSBiz
Released with Version	V2R6.2
ITSP Features & Capabi	ilities
Account (DID/Client)	DID
Multisite	
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no



Remarks:

BITel delivers an access device, IP address of access device needs to be configured as Proxy and Registrar

¹⁾ Clip no Screnning needs to be booked at BITel

System	OpenScape Business
Released with Version	V3R3
BITel Business SIP Flex	x Features & Capabilities
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

Remarks:

SIP-Trunk BITel Business SIP Flex is released for:

- OpenScape Business V3 Mainboard Familiy
- OpenScape Business S



3.13.6. **CITEC Universe SIP Trunk**



System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes, with single registration
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no 1)
Secure trunk	no

Remarks:

1) T.38 MUST be deactivated in the system



3.13.7. <u>Datel</u>





Remarks:

¹⁾ The certification is valid for the DATEL Phone&Surf SIP Trunk product. Other products (e.g. MSN based) are available but not yet certified with OpenScape Business

²⁾ Clip no Screening needs to be boocked at DATEL



3.13.8. <u>Deutsche Telefon</u>



System	OSBiz	
Released with Version	V2R3	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes – single trunk / dedicated trunks	
CLIP / CLIR	yes / yes	
COLP	-	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / -	
T.38 Fax	yes	

Remarks:

"Einzelverbindungsnachweis": The number presented in PAI will be used in the EVN. If the individual number should be presented in EVN the CLIP no Screening feature must be deactivated.



3.13.9. **easybell**



System	OSBiz
Released with Version	V2R6
ITSP Features & Capab	ilities
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes 1)
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks:

Changed default settings introduced in V2R7, please check the configuration document for details (CLIPnoScreening)

¹⁾ CLIP no screening must be activated in customer portal of easybell (see configuration description)



3.13.10. **EasyFone**

System	OSBiz	
Released with Version	V3R2	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes - single trunks	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	optional	
secure trunk	no	



Remarks:

- The EasyFone SIP Trunk requires a static public IP address.
- The possibility of sending or receiving T.38 faxes depends on the characteristics of the remote station and the transmission may take place with G.711.
- Automatic use of the backup SIP trunk is currently not supported.



3.13.11. ecotel sipTrunk 2.0

System	OSBiz	
Released with Version	V3R1.2	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes - single trunk	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes 1)	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	no	
Secure trunk	no	



Remarks:

1) CLIP no screening needs to be booked



3.13.12. **ennit**

Profile maintained for existing installations. A new profile with updated settings is available "TNG Stadtnetz"

3.13.13. **envia TEL**

System	OpenScape Business	
Released with Version	V3R2	
envia TEL enVoice IP ra	nge Features & Capabilities	
Account (DID/Client)	DID	
Multisite	no	
CLIP / CLIR	yes	
CLIP no Screening	yes 1)	
COLP	yes	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711	yes	
Codecs G729	no	
T.38 Fax	no	
Secure trunk	no	



Anmerkungen:

¹⁾ CLIP no Screening ist ein kostenpflichtiges Leistungsmerkmal und muss gesondert beauftragt werden. Die Nutzung ist im Profil voreingestellt.

3.13.14. **equada**

System	OsBiz
Supported since version	V2_R0.3.11
	24
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	√/-
T.38 Fax	$\sqrt{}$



3.13.15. <u>ewe</u>

The profile is valid for *EWE* (https://www.swb.de/) and *osnatel* (https://www.osnatel.de/).

System	OpenScape Business	
Released with Version	V2R6	
update	V3R3	
EWE Voice+ SIP Trunk	Features & Capabilities	
Account (DID/Client)	DID	
Multisite	dedicated trunk 1)	
CLIP / CLIR	yes/yes	
CLIP no Screening	yes ²⁾	
COLP	yes	
Call Forwarding (302)	yes	
DTMF (RFC2833/4733)	yes	
Codecs G722/G711/G729	yes /yes / no	
T.38 Fax	yes ³⁾	
Secure trunk	no	



Remarks:

¹⁾ Depending on customers Call Attempts per Second "Multsite" is available for a second trunk and requires confirmation of EWE TEL GmbH.

²⁾ Clip no Screening needs to be activated by the provider.

³⁾ T.38 is support in transport mode only. If a destination supports T.38 fax will be transported in T.38, if interworking to TDM is needed or destination does not support T.38 the fax is transmitted by G.711.



3.13.16. **Gamma**

System	OpenScape Business	
Released with Version	V3R3	
Gamma NGN (DE)	Features & Capabilities	
Account (DID/Client)	DID	
Multisite	yes - dedicated trunk	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	yes	
Secure trunk	no	



Remarks:

T.38 is not released with OpenScape Business V3R3.

3.13.17. **gmx**

System	OSBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	V
Codecs G.711/G.729	√/?
T.38 Fax	-



3.13.18. **gnTel** for details on gnTel see the table gnTel



3.13.19. **Helinet**

System	OpenScape Business	
Released with Version	V3R3	
	Features & Capabilities	
Account (DID/Client)	DID	
Multisite	no	
CLIP / CLIR	yes	
CLIP no Screening	yes ¹⁾	
COLP	yes	
Call Forwarding (302)	yes	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	no	
Secure trunk	no	



Remarks:

¹⁾ CLIP no Screening can be booked optional



HFO - Germany 3.13.20.

System	OsBiz
Supported since version	V2_R0.3.11
	24
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	•
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	√/-
T.38 Fax	$\sqrt{}$

For security reasons OpenScape Business uses dedicated SIP server ports for internal (5060) and external (5070) traffic. HFO can handle SIP traffic on port 5060 only. Due to this limitation, the external SIP port in Openscape Business **MUST** be configured to 5060.

3.13.21. **HL komm**



System	OSBiz	
Released with Version	V2R3	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes - dedicated trunks	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes 1)	
COLP	-	
Call Forwarding (302)	yes	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / -	
T.38 Fax	-	
Secure trunk	no	



3.13.22.

System	OSBiz
Released with Version	V2R6.2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	??
CLIP / CLIR	yes / yes
CLIP no Screening	yes 1)
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no



Remarks:

htp delivers an access device, IP address of access device needs to be configured as Proxy and Registrar

¹⁾ Clip no Screening needs to be booked at htp.

System	OpenScape Business
Released with Version	V3R3
	Features & Capabilities
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes
CLIP no Screening	yes
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

Remarks:

htp Business FleX SIP-Trunk smart is released for following OpenScape Business variants:

- OpenScape Business V3 Mainboard Familiy
- OpenScape Business S



3.13.23. <u>Inexio</u>



System	OSBiz
Released with Version	V2R5.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Issue 96



3.13.24. komroVolP-Trunk

System	OpenScape Business
Released with Version	V3R3
	Features & Capabilities
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes
CLIP no Screening	yes 1)
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes ²⁾
Secure trunk	no



Remarks:

¹⁾ CLIP no Screening can be booked optional

²⁾ The option of sending or receiving T.38 faxes depends on the properties of the remote station and is only available within the komro network and only for IP system connections with an activated T.38 codec.



3.13.25. <u>M-Net Premium</u>

System	OSBiz
Released with Version	V2R3.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	Not Supported by OSBiz (dedicated transport needed)
CLIP / CLIR	yes / yes
COLP	no
CLIP no Screening	yes (with costs)
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure Trunk	released later



Remarks:

If the Calling Party Number should be forwarded in case of diversion, CLIP no Screening needs to be booked as an optional feature.

For details see the configuration guide in wiki

Issue 96



3.13.26. MK Netzdienste

System	OSBiz
Released with Version	V2R0
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	?
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no



Remarks:

Clip no Screening needs to be booked at provider.

Updated profile with V2R6.2 available



3.13.27. NetCologne ProPhone SIP



System	OSBiz
Released with Version	V2R7
ITSP Features & Capab	ilities
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no

Remarks:

OpenScape Business must be connected with a dedicated VoIP router using the WAN interface in TCP/IP mode. Internet traffic needs to be routed via a different router. See the configuration description for details.



3.13.28. NetCom BW



System	OSBiz
Released with Version	V2R6
ITSP Features & Capabilities	
Account (DID/Client)	DID 1)
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks:

Netcom BW delivers an access device, the IP-address of the access device needs to be configured, thus the profile needs to be completed during configuration of the system

For security reasons OpenScape Business uses dedicated SIP server ports for internal (5060) and external (5070) traffic. To ensure symmetric UDP traffic without registration the external SIP port in Openscape Business MUST be configured to 5060.

UC is not tested and released with Netcom BW

Issue 96

^{1) =} without registration



3.13.29. **NFON**

System	OSBiz	
Released with Version	V2R3.1	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	no yet available / coming soon	
CLIP / CLIR	yes / yes	
COLP	no	
CLIP no Screening	yes	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	yes	





3.13.30. **O2 All-IP Voice SIP**

2

System	OSBiz
Released with	V2R2.2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	multiple registration performed by CNG
CLIP / CLIR	yes / yes
COLP	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	_1)

Remarks:

O₂ delivers a Corporate Network Gateway (CNG) which is used to terminate the SIP trunk. OpenScape Business cannot be connected directly without CNG (using the O₂ Gm-Interface)

OpenScape Business must be connected with the CNG using the WAN interface in TCP/IP mode.

During setup of the ITSP trunk the customer specific CNG IP address needs to be configured in OpenScape Business.

For security reasons OpenScape Business uses dedicated SIP server ports for internal (5060) and external (5070) traffic. The CNG can handle SIP traffic on port 5060 only. Due to this limitation, the external SIP port in OpenScape Business MUST be configured to 5060.

¹⁾ T.38 is support in transport mode only. If a destination supports T.38 fax will be transported in T.38, if interworking to TDM is needed or destination does not support T.38 the fax is transmitted by G.711



3.13.31. **omnidat**



System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes (registration for each location)
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

Remarks:

Clip no Screnning needs to be booked and payed:

3.13.32. Peoplefone AG (DE)

System	OsBiz
Supported since version	V2_R0.3.0
Provider	
SIP DID account	
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	V/V
T.38 Fax	-

Issue 96



3.13.33. PhoneVoice

System	OSBiz
Released with Version	V2R5
ITSP Features & Capab	ilities
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no



3.13.34. *purtel*

System	OSBiz
Released with Version	V1R1
ITSP Features & Capabi	lities
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	Yes 1)
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no T.38 Fax service stopped on 01.01.2020
Secure trunk	no



Remarks:

Customer specific profile entries are needed for Domain name, Registrar and Proxy.

Updated profile with V2R7.1 available

¹⁾ CLIP no screening must be activated in customer portal



3.13.35. Plusnet IPfonie Extended

plusnet

System	OsBiz
Supported since version	QSC: V1_R1.1.0
	Plusnet: V2R7
Provider	
IPfonie (DID)	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	\ \ \ \ \ \
T.38 Fax	√

Plusnet IPfonie extended replaces the previously used QSC profile which is not longer available.

3.13.36. Plusnet IPfonie Extended Connect



System	OSBiz
Released with Version	QSC: V1R3.1 Plusnet: V2R7
ITSP Features & Capabi	lities
Account (DID/Client)	DID
Multisite	yes (single registration)
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes 1)
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	yes (but not yet released)

Remarks:

Plusnet has taken over all activities from QSC AG. By end of 2019 Plusnet is no longer allowed to use the QSC brand. Thus new profiles are available in OpenScape Business. Please check the configuration document and the information you have received from Plusnet.

¹⁾ Only Payload Type 101 supported -> System and SIP endpoints **MUST** be configured accordingly



3.13.37. *reventix*

System	OSBiz	
Released with Version	V2R6.2	
ITSP Features & Capab	ilities	
Account (DID/Client)	DID	
Multisite	yes 1)	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	yes	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	yes	
Secure trunk	no	



Remarks:

3.13.38. <u>rgi VoIP Trunk 200</u>

System	OSBiz	
Released with Version	V3R1.2	
ITSP Features & Capab	ilities	
Account (DID/Client)	DID	
Multisite	no	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	no	
Secure trunk	no	



¹⁾ Depending on customer needs one or several registrations are used.



3.13.39. **R-Kom**



System	OSBiz
Released with Version	V3
ITSP Features & Capabili	ities
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes (needs to be payed)
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no

3.13.40. <u>sipgate</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
sipgate trunking (DID)	
sipgate basic (MSN)	
Features	
CLIP / CLIR	V
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	V / V
T.38 Fax	-



3.13.41. **Steffel-Voice**



System	OSBiz
Released with Version	V2R7
ITSP Features & Capab	ilities
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	no

Remarks:

Clip no Screnning need to be configured/booked at ITSP.

Updated profile with V2R7.1 available



3.13.42. Tele AG



System	OSBiz
Released with Version	V3
ITSP Features & Capab	ilities
Account (DID/Client)	DID 1)
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
CLIP no Screening	yes ²⁾
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no

Remarks:


Issue 96

¹⁾ The certification is valid for the Tele AG SIP Trunk product. Other products (e.g. MSN based) are available but not yet certified with OpenScape Business.

 $^{^{\}rm 2)}$ Clip no Screening needs to be boocked at Tele AG



3.13.43. *TeleData*





Remarks:

¹⁾ optional feature, needs to be booked at TeleData

²⁾ TeleData does not provide media gateways, thus the support of RFC2833 telephone events depends on the connection partner. **UC-Suite cannot be released with this ITSP.**



3.13.44. <u>Telekom CompanyFlex SIP Trunk</u>

System	OSBiz
Released with Version	V2R7.1
ITSP Features & Capab	ilities
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
CLIP no Screening	yes 1)
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes
Secure trunk	yes



Remarks:

The Telekom CompanyFlex SIP-Trunk profile is also suitable for the *T-Systems Corporate CompanyFlex* product offered by T-Systems as all trunks are operated on the same platform:

¹⁾ Clip no Screening needs to be booked at ITSP (please check configuration document)



3.13.45. <u>Telekom IP-As mit MSN</u>

System	OsBiz
Supported since version	V1_R2.1
Provider	
SIP DID account	-
SIP Client account	
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{I}\sqrt{I}$
T.38 Fax	-(P)



The *Telekom IP-As mit MSN* profile is suitable for the following products offered by Telekom and T-Systems as all trunks are operated on the same platform :

- 3.13.45.1. Telekom DeutschlandLAN IP Start
- 3.13.45.2. Telekom DeutschlandLAN IP Voice/Data
- 3.13.45.3. T-Systems Corporate call Start
- 3.13.45.4. T-Systems Corporate IP Voice/Data



3.13.46. <u>Telekom DeutschlandLAN SIP-Trunk Registered Mode</u>

System	OSBiz
Released with Version	V2R2
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
COLP	no
CLIP no Screening	yes (with costs)
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes 2)
Secure Trunk	yes



Remarks:

The Telekom DeutschlandLAN SIP-Trunk profile is suitable for the following products offered by T-Systems as all trunks are operated on the same platform.

T.38 is support in transport mode only. If a destination supports T.38 fax will be transported in T.38, if interworking to TDM is needed or destination does not support T.38 the fax is transmitted by G.711



3.13.47. **TelemaxX**

System	OSBiz
Released with Version	V3R0.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	yes



Remarks:

TelemaxX delivers an access device which must be connected to the WAN interface. Please check the configuration hints about static route configuration.



3.13.48. **T-Systems Corporate SIP Trunk**

Individual profile for the specific customer requirements based on a Project Specific Release.

Please contact: osbiz-certification@atos.net.





3.13.49. <u>teliko</u>



System	OSBiz
Released with Version	V2R7.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes 1)
COLP	no
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no ²)
Secure trunk	no

Remarks:

¹⁾ Clip no Screnning need to be booked at Teliko

²⁾ For best interoperability T.38 MUST be deactivated in the OpenScape Business system



3.13.50. TNG Stadtnetz

System	OSBiz
Released with Version	V2R7
ITSP Features & Capab	ilities
Account (DID/Client)	DID
Multisite	yes - dedicated trunks
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes 1)
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no



Remarks:

Profile is used for different carriers; thus domain, proxy and registrar need to be configured manually. See configuration description.

TNG must configure "national number format" of calling party for incoming local calls. The TNG default of "local number format" is not supported by OpenScape Business.

3.13.51. **Toplink**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	$\sqrt{I}\sqrt{I}$
T.38 Fax	-

¹⁾ Call deflection needs to be booked at TNG



3.13.52. **Unitymedia**

System	OSBiz
Released with Version	V3
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes 1)
T.38 Fax	yes
Secure trunk	no



Remarks:

¹⁾ G729 only endpoints are not supported due to problems with transfer scenarios.



3.13.53. <u>Vodafone Anlagenanschluss R4</u>

System	OSBiz
Released with Version	V2R7 update with V3R2
ITSP Features & Capab	ilities
Account (DID/Client)	DID 1)
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	optional ²⁾ only for SIP end-to-end connections
Secure trunk	yes ³⁾



Remarks:

Vodafone will use customer specific server addresses; thus the profile needs to be completed during configuration of the system

For security reasons OpenScape Business uses dedicated SIP server ports for internal (5060) and external (5070) traffic. You have to either request the usage of port 5070 at Vodafone or configure the external SIP port = 5060 in OpenScape Business.

Please check the configuration description available in Wiki.

¹⁾ without registration

²⁾ The option of sending or receiving T.38 faxes depends on the properties of the remote station and is only available within the Vodafone network and only for IP system connections with an activated T.38 codec. T.38 in conjunction with encryption is not practically possible since T.38 terminals generally use UDPTL and not RTP.

³⁾ requires manual setting in expert mode (since V3R2)



3.13.54. **Vodafone Anlagenanschluss R5**

System	OpenScape Business
Released with Version	V3R3
	Features & Capabilities
Account (DID/Client)	DID
Multisite	yes - single trunk
CLIP / CLIR	yes
CLIP no Screening	yes
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes
T.38 Fax	optional only for SIP end-to-end connections
Secure trunk	yes



Remarks:

The option of sending or receiving T.38 faxes depends on the properties of the remote station and is only available within the Vodafone network and only for IP system connections with an activated T.38 codec. T.38 in conjunction with encryption is not practically possible since T.38 terminals generally use UDPTL and not RTP.



3.13.55. **Voiceworks DE**



System	OSBiz
Released with Version	V3R1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes /no
T.38 Fax	yes
Secure trunk	no



3.13.56. <u>wilhelm.tel</u>



System	OSBiz
Released with Version	V3
ITSP Features & Capab	oilities
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no ¹⁾
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no ²⁾
Secure trunk	no

Remarks:

³⁰² is supported by wilhelm.tel but the required signaling variant (different call number formats in 302 and basic call) is not supported by OpenScape Business

²⁾ T.38 MUST be deactivated in the system (see configuration document)



3.13.57. <u>wittenberg-net GmbH</u>

System	OpenScape Business
Released with Version	V3R3
wittenberg-net GmbH	Features & Capabilities
Account (DID/Client)	DID
Multisite	yes - dedicated trunk
CLIP / CLIR	yes
CLIP no Screening	yes 1)
COLP	yes
Call Forwarding (302)	yes
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	no
Secure trunk	no



Remarks:

¹⁾ CLIP no Screening is optional and can be booked to show the calling party number with call forwarding.

Call data is recorded centrally for the account.



3.13.58. **WOBCOM**



System	OSBiz	
Released with Version	V3	
ITSP Features & Capabilities		
Account (DID/Client)	DID 1)	
Multisite	no	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	yes	
DTMF (RFC2833/4733)	yes ²⁾	
Codecs G711/G729	yes / no	
T.38 Fax	no ³⁾	
Secure trunk	no	


Remarks:


- ¹⁾ WOBCOM offers DID (Anlagenanschluß) and MSN (Teilnehmeranschluß) type of trunks. The certification is valid for the DID type only.
- ²⁾ RFC2833 is randomly supported. RFC2833 was not offered in several testcases during certification testing, thus UC is not released with WOBCOM. Please check the configuration document for limitations.
- 3) T.38 must be deactivated in the system



3.14. Greece

3.14.1. **COSMOTE**








Overview about released SIP Providers



3.15. Hungary

3.15.1. Netfone Telecom





Remarks:

¹⁾ CLIR is supported through service code towards ITSP.

²⁾ T.38 is not supported by Netfone and MUST be deactivated in the system.



3.16.Hong Kong

3.16.1. Hong Kong Broadband Network

System	OSBiz	
Released with Version	V2R3	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite		
CLIP / CLIR	√ / - ¹)	
COLP	-	
DTMF (RFC2833/4733)	V	
Codecs G711/G729	\sqrt{N}	
T.38 Fax	√ 2)	



Remarks:

¹⁾ CLIR settings in profile are set properly, however provider ignores them at the moment and use another way to activate the CLIR for outgoing calls. See configuration example

²⁾ Problem with UC fax calls when other party has ECM enabled. Although the negotiation in T38 is done with ECM off, it looks that somehow ITSP still expects (ECM). Investigated in ITSP side. When ECM is disabled at other side, then problem is not occurring any more.



3.16.2. **HGC**



System	OSBiz	
Released with Version	V2R5	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	no	
CLIP / CLIR	yes / yes 1)	
CLIP no Screening	no	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes ²⁾	
T.38 Fax	no ³⁾	
Secure trunk	no	

Remarks:

Please read the configuration documentation for the following special settings required for correct operation :

- VAD MUST be actiavted for all codes at VoiceGateway settings
- Reduntant Transmition of RFC2833 MUST be disabled (default since V2R5)
- SIP EXT port MUST be changed to 5061
- Incoming call To header conveys only the subscriber number

¹⁾ CLIR is supported only with dailing the prefix '133' in front of the external number.

²⁾ Officially ITSP is not supporting G729 (annexb=no) but can be offered under customer specific request. Codec is still available in SDP.

³⁾ T38 is not officially supported. However, for incoming Fax calls, OSBiz renegotiates for T38 and ITSP may accept it.



3.17.Italy

3.17.1. **Broadcloud**

see Broadcloud Germany - France - Italy - UK - Australia - USA

3.17.2. <u>Infracom</u>

System	OsBiz
Supported since version	V1_R1.1.
	0
Provider	
SIP DID account	-
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	$\sqrt{}$
DTMF (RFC 2833)	-
Codecs G.711/G.729	√/-
T.38 Fax	-

Note

There is an open issue with displaying international number format. Display, caller list and callback are not working correctly, because provider is not sending this in standard format.

3.17.3. **TWT**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	
SIP Client account	
Features	
CLIP / CLIR	
COLP	√/ -
DTMF (RFC 2833)	
Codecs G.711/G.729	√/-
T.38 Fax	V



3.17.4. **Viatek**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√ *1)
SIP Client account	√ *1)
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	V/V
T.38 Fax	V

^{*1)} manual configuration of SIP server addresses necessary

3.18.Lichtenstein

3.18.1. **FL1 Telecom**

System	OsBiz
Supported since version	V2_R2.0.0
Provider	
SIP DID account	√*1)
SIP Client account	
Features	
CLIP / CLIR	$\sqrt{/}$
COLP	ı
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{I}\sqrt{I}$
T.38 Fax	$\sqrt{}$
Multisite	√*2)

^{*1)} manual configuration of SIP server addresses necessary

3.19.Luxembourg

3.19.1. <u>IPnexia</u>

for details on IPnexia see the table IPnexia Belgium



^{*2)} Supported, single registration can handle all sites (but not tested)



3.20.Mexico

3.20.1. <u>Telefonica</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	$\sqrt{}$
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	V / V
T.38 Fax	V

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.



3.21.Netherlands

3.21.1. **BCOM**

System	OSBiz	
Released with Version	V2R1	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	yes (since V2R5.1)	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	no	
Secure trunk	no	



3.21.2. BLU Networks

System	OSBiz	
Released with Version	V2R2 / update in V2R7	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	yes	
Secure trunk	no	



Remarks:


Profile update with V2R7



3.21.3. **Deanconnect B.V.**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	

3.21.4. **gnTel**



Remarks:



¹⁾ Emergency calls are routed based on the calling party number

²⁾ G.729 is available as an option which needs one time payment



3.21.5. <u>infopact</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	

3.21.6. KPN VoiPConnect,

System	OsBiz
Supported since version	V2 R2.1.0_262
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{/}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	√/-
T.38 Fax	V

kpn

3.21.7. KPN TLS NL (KPN EEN over TLS)

System	OSBiz	
Released with Version	V3R1.2	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes - single trunk	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	yes	





Secure trunk	ves
Secure trunk	yes

3.21.8. <u>Motto Communications</u>

System	OsBiz
Supported since version	V2_R1
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{/}$
COLP	$\sqrt{}$
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-

Note: G722 is supported by ITSP

3.21.9. OneCentral

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	ı
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-

Note:

OneCentral is released for SIP MEX feature (available only in OSBiz since V1R3.4 and later sw version)

3.21.10. **OneXS**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	
SIP Client account	
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V



3.21.11. <u>Pocos</u>

System	OSBiz	
Released with Version	V3R1.2	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes - single trunk	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	yes	
Secure trunk	no	



3.21.12. **RoutIT**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	
SIP Client account	-
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	√ /-
T.38 Fax	



3.21.13. **RoutIT TLS**

System	OpenScape Business	
Released with Version	V3R3	
	Features & Capabilities	
Account (DID/Client)	DID	
Multisite	yes - single trunk	
CLIP / CLIR	yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	yes	
Secure trunk	yes	



3.21.14. **Scaldis B.V.**

System	OSBiz	
Released with Version	V3R1.2	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes - single trunk	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	yes	
Secure trunk	no	





3.21.15. **SIGNET B.V**

System	OsBiz
Supported since version	V2_R2.0.1_251
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{/}$
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	\sqrt{N}
T.38 Fax	
Multisite	



3.21.16. **Speakup**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-

3.21.17. <u>tele2</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V

3.21.18. **<u>T-Mobile</u>**

System	OsBiz
Supported since version	V2_R0.3.1124
Provider	
SIP DID account	
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V



3.21.19. <u>Vodafone</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	
SIP Client account	
Features	
CLIP / CLIR	
COLP	
DTMF (RFC 2833)	√-
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	

3.21.20. Voiceworks NL

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	\checkmark
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	√/ -
T.38 Fax	-



3.21.21. Voiceworks MEX

System	OSBiz	
Released with Version	V2R3	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	Yes / supported with singe registration	
CLIP / CLIR	yes / not relevant 1)	
COLP	-	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	not relevant 1)	



Remarks:

Mobile phone integration with SIP-MEX

¹⁾ The certification is done with SIP-MEX in a mode where only SIP-MEX users could use the ITSP route. Consequently, some features (like CLIR) or calls (like fax calls) were unable to be set/used and were not relevant.

3.21.22. **VoipQ**

System	OSBiz
Released with Version	V3R0.1
ITSP Features & Capabi	lities
Account (DID/Client)	DID
Multisite	no
CLIP / CLIR	yes / yes
CLIP no Screening	yes 1)
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / no
T.38 Fax	yes
Secure trunk	no



Remarks:

¹⁾ deactivated in default, need to be booked at provider



3.21.23. **VoIPXS**

System	OSBiz	
Released with Version	V2R5	
ITSP Features & Capabi	lities	
Account (DID/Client)	DID	
Multisite	Yes / single registration for all sites 1)	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	yes	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes ²⁾	
T.38 Fax	yes	
Secure trunk	Not yet released with OSBiz	



Remarks:

3.21.24. **X2COM**

System	OSBiz
Released with Version	V2R1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	yes (since V2R5.1)
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no
Secure trunk	no



¹⁾ Emergency calls are routed based on the calling party number

²⁾ G.729 is available as an option which needs onetime payment



3.21.25. **Ziqqo**

System	OsBiz
Supported since version	V1_R3.2
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	√/ -
T.38 Fax	V

Ziggo is available for existing installations. The profile should not be used for new installations

3.21.26. **Vodafone Ziggo**

System	OSBiz
Released with Version	V2R5.1
ITSP Features & Capabilities	
Account (DID/Client)	DID
Multisite	yes
CLIP / CLIR	yes / yes
CLIP no Screening	yes
COLP	no
Call Forwarding (302)	no
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	no¹)
Secure trunk	no

vodafone 🔾 ZIGGO

Remarks:

¹⁾T.38 is not supported by Vodafone Ziggo and MUST be deactivated in the system.



3.22.New Zealand

3.22.1. <u>Orcon Ltd</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	$\sqrt{}$
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	

3.22.2. <u>TelstraClear</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	$\sqrt{}$
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	√/-
T.38 Fax	-



3.22.3. voyager



System	OSBiz	
Released with Version	V2R7	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	yes	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	yes	
Secure trunk	no	

Remarks:

Customer specific profile entries are needed for domain, registrar and proxy



3.23.Portugal

3.23.1. Altice (Portugal Telecom)



System	OSBiz	
Released with Version	V2R6	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes	
CLIP / CLIR	yes / yes	
CLIP no Screening	no	
COLP	no	
Call Forwarding (302)	yes	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	yes	
Secure trunk	no	

Remarks:

For security reasons OpenScape Business uses dedicated SIP server ports for internal (5060) and external (5070) traffic. Altice handle SIP traffic on port 5060 in default, thus the external SIP port in Openscape Business MUST be configured to 5060. Please check the configuration document.

3.23.2. **G9 Telecom**

System	OSBiz	
Released with Version	V3R2.1	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes - single trunk	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	no	
Secure trunk	no	





3.23.3. **Portugal Telecom**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	•
Features	
CLIP / CLIR	√/-
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	$\sqrt{}$

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.

3.23.4. **Vodafone**

System	OpenScape business	
Released with Version	V2R5	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes 1)	
CLIP / CLIR	yes / yes	
COLP	no	
CLIP no screening	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	no ¹⁾	
Secure trunk	no	



Remarks:

Vodafone will use customer specific server addresses, thus the profile needs to be completed during configuration of the system

¹⁾ Vodafone can give different numbers from different locations in one single registration

²⁾ T.38 is not supported by Vodafone and MUST be deactivated in the system



3.24. Saudi Arabia

3.24.1. Saudi Telecom Company

System	OSBiz	
Released with Version	V2R6	
ITSP Features & Capabilities		
Account (DID/Client)	DID 1)	
Multisite	no	
CLIP / CLIR	yes ²⁾ / yes	
CLIP no Screening	no	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	no	
Secure trunk	no	

Remarks:

Customer specific profile entries are needed for proxy address

For security reasons OpenScape Business uses dedicated SIP server ports for internal (5060) and external (5070) traffic. STC handle SIP traffic on port 5060 in default, thus the external SIP port in Openscape Business MUST be configured to 5060. Please check the configuration guide for details

UC is not tested and released with STC

¹⁾ No registration is used

²⁾ the calling party is represented in implicit format for national and international calls, for that reason international calls are presented with the wrong prefix in caller list and applications



3.25. Serbia

3.25.1. Orion Telekom

System	OsBiz
Supported since version	V1_R3.2.0
Provider	
SIP DID account	√ *1)
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	V / V
T.38 Fax	-

^{*1)} without registration

3.25.2. <u>Telenor</u>

System	OsBiz
Supported since version	V1_R3.3.0
Provider	
SIP DID account	√ *1)
SIP Client account	ı
Features	
CLIP / CLIR	√/-
COLP	ı
DTMF (RFC 2833)	V
Codecs G.711/G.729	$\sqrt{I}\sqrt{I}$
T.38 Fax	$\sqrt{}$

^{*1)} without registration



3.26.Slovakia

3.26.1. **Slovak Telekom**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√ *1)
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-

1) without registration

Restrictions from Certification: Semi-Attended Transfer with 2 PSTN fails → ITSP error No MoH when SIP holds PSTN fails → ITSP error

3.27.Slovenia

A1 SIP Trunk 3.27.1.

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	V/ V
T.38 Fax	-

3.27.2. **Detel**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-



3.27.3. **MegaM**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	V
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	$\sqrt{I}\sqrt{I}$
T.38 Fax	-

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.

3.27.4. <u>T-2</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√
SIP Client account	-
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	$\sqrt{1}\sqrt{1}$
T.38 Fax	-

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.

3.27.5. <u>Telemach</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-



3.28. South Africa

3.28.1. Nashua NCN

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	
Features	
CLIP / CLIR	
COLP	
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	

3.28.2. <u>Vodacom</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	\checkmark
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.

Issue 96



3.29.Spain

3.29.1. **LCR**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	\checkmark
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	V
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	$\sqrt{}$

3.29.2. **Telecable**

System	OsBiz
Supported since version	V2R1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V

3.29.3. <u>vozelia</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	-/√
T.38 Fax	-



3.29.4. **VozTelecom**

System	OsBiz
Supported since version	V2_R2.0.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	
Features	
CLIP / CLIR	$\sqrt{/}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V
Multisite	-



3.30.Sweden

3.30.1. <u>Tele2</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	√ *1
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	V/V
T.38 Fax	-

^{*1} no registration / static IP is used

Note: Tele2 is released for SIP MEX feature (available only in OSBiz since V1R3)

3.30.2. <u>Telia</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	-
Codecs G.711/G.729	√/ -
T.38 Fax	√*1

^{*1 =} only outgoing



3.31.Switzerland

E-fon AG 3.31.1.

System	OsBiz
Supported since version	V1_R3.3.553
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-

3.31.2. **Improware**

System	OSBiz	
Released with Version	V3	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	not relevant in SWZ	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes 1)	
COLP	no	
Call Forwarding (302)	yes	
DTMF (RFC2833/4733)	yes ²⁾	
Codecs G711/G729	yes / no	
T.38 Fax	yes	
Secure trunk	no	

Remarks:



Issue 96

¹⁾ Clip no Screnning needs to be booked at ITSP (one time fee) ²⁾ RFC2833 payload type MUST be set to 101 in the system



3.31.3. Nexphone



System	OSBiz	
Released with Version	V3	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite	yes	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	yes	
DTMF (RFC2833/4733)	yes 1)	
Codecs G711/G729	yes / yes	
T.38 Fax	no ²⁾	
Secure trunk	no	

Remarks:

3.31.4. Peoplefone AG (CH)

System	OsBiz
Supported since version	V2_R0.3.0
Provider	
SIP DID account	V
SIP Client account	-
Features	
CLIP / CLIR	V
COLP	-
DTMF (RFC 2833)	V
Codecs G.711/G.729	$\sqrt{I}\sqrt{I}$
T.38 Fax	-

¹⁾ Nexphone does not support RFC2833 negotiation. RFC2833 payload type MUST be configured with 101 in the system and connected SIP devices

²⁾ T.38 MUST be deactivated in the system



3.31.5. <u>sipcall</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	-
SIP Client account	
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	V
Codecs G.711/G.729	V/V
T.38 Fax	V

ITSP certified, but no profile provided in system. Manual configuration of servers according to the ITSP description is needed using the default profile as base template.



3.31.6. **Sunrise**

System	OSBiz	
Released with Version	V1R3.3 update with V3R0.1	
ITSP Features & Capabilities		
Account (DID/Client)	DID	
Multisite		
CLIP / CLIR	yes / yes	
CLIP no Screening	yes	
COLP	no	
Call Forwarding (302)	yes	
DTMF (RFC2833/4733)	yes 1)	
Codecs G711/G729	yes / no	
T.38 Fax	no	
Secure trunk	no	



¹⁾ only Payload Type 101 is supported -> OSBiz and SIP endpoints must be configured accordingly



3.31.7. Swisscom BCON

System	OsBiz
Supported since version	V1_R3.3.55
	3
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	√ 1)
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-

¹⁾ Only Payload Type 101 supported -> System and SIP endpoints has to be configured accordingly

3.31.8. <u>Swisscom Enterprise SIP</u>

System	OsBiz
Supported since version	V2_R2.0.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	
Features	
CLIP / CLIR	\sqrt{N}
COLP	$\sqrt{}$
DTMF (RFC 2833)	√ 1)
Codecs G.711/G.729	$\sqrt{I}\sqrt{I}$
T.38 Fax	
Multisite	Supported

¹⁾ Only Payload Type 101 supported -> System and SIP endpoints has to be configured accordingly



3.31.9. <u>Swisscom Smart Business Communication</u>

System	OsBiz
Supported since version	V2_R0.3.0
Provider	
SIP DID account	
SIP Client account	-
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	√ 1)
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	V

¹⁾ Only Payload Type 101 supported -> System and SIP endpoints has to be configured accordingly

3.31.10. Swisscom VoipGate

System	OsBiz
Supported since version	V2_R0.3.xx
	X
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	ı
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	√ 1)
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	

¹⁾ Only Payload Type 101 supported -> System and SIP endpoints has to be configured accordingly

3.31.11. Telco Pack SA

System	OsBiz
Supported since version	V1_R3.3
Provider	
SIP DID account	
SIP Client account	-
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{I}\sqrt{I}$
T.38 Fax	V



3.31.12. **UPC CH Internet Registration**



System	OSBiz	
Released with Version	V2R7.1	
ITSP Features & Capabi	lities	
Account (DID/Client)	DID	
Multisite	yes	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes 1)	
COLP	yes	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	no	
Secure trunk	no	

Remarks:

Please check the configuration description for details about T.38 and DTMF configuration.

¹⁾ need to be booked at UPC



3.31.13. **UPC CH Internet Static IP**



System	OSBiz	
Released with Version	V2R7.1	
ITSP Features & Capab	ilities	
Account (DID/Client)	DID	
Multisite	yes	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes 1)	
COLP	yes	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / no	
T.38 Fax	no	
Secure trunk	no	

Remarks:

Please check the configuration description for detailes about Port, T.38 and DTMF configuration.

The formerly defined Cablecom profile is no longer available in OpenScape Business.

3.31.14. <u>vtx</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	V
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{I}\sqrt{I}$
T.38 Fax	-

¹⁾ need to be booked at UPC



3.32.United Kingdom

3.32.1. **Broadcloud**

see Broadcloud Germany - France - Italy - UK - Australia - USA

3.32.2. **BT IPVS**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	\checkmark
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	

BT IPVS is available for existing installations. The profile should not be used for new installations



3.32.3. BT Wholesale SIP Trunking

5.52.5. <u>DI Wilolesale Si</u>	T Trunking	BT wholesale
System	OSBiz	D Wilolesale
Released with Version	V2R4.1	
ITSP Features & Capabilit	ies	
Account (DID/Client)	DID 1)	
Multisite	yes ²⁾	
CLIP / CLIR	yes / yes	
CLIP no Screening	yes 3 ⁾	
COLP	-	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes 4 ⁾	
Codecs G711/G729	yes / yes	
T.38 Fax	yes	
Secure trunk	no	

Remarks:

A static IP is a prerequisite to connect to the BT Wholesale SIP Trunking service. Please see the configuration descripiton for details.

¹⁾ No registration is used

²⁾ the service can provide multiple unrelated number ranges on the same trunk

³⁾ CLIP no Screening is supported if the number is pre-approved by BT but not in call diversion scenarios.

⁴⁾ Currently the service doesn't ensure that all DTMF sent as RTP events, meaning another SIP customer may send you in-band tones only. However, later this year BT will be adding in the functionality for DTMF destined for a customer to be RTP events only.



3.32.4. **BT Wholesale Hosted Communications**




System	OSBiz	
Released with Version	V4.1	
ITSP Features & Capabilit	ies	
Account (DID/Client)	DID	
Multisite	yes	
CLIP / CLIR	yes / yes	
CLIP no Screening	no	
COLP	no	
Call Forwarding (302)	no	
DTMF (RFC2833/4733)	yes	
Codecs G711/G729	yes / yes	
T.38 Fax	yes	
Secure trunk	no	

Remarks:

There are a suite of features provided at a trunk level which can be used to introduce additional functionality to the ITSP, however, there are limitations on which features are and are not supported with OpenScape Business. Please check the configuration document for details



3.32.5. **Gamma**





Remarks:

Customer specific profile entries are needed for proxy address

A static IP is a prerequisite to connect to Gamma.

For security reasons OpenScape Business uses dedicated SIP server ports for internal (5060) and external (5070) traffic. Gamma handle SIP traffic on port 5060 in default, thus the external SIP port in Openscape Business MUST be configured to 5060.

Updated profile with V2R7.1 available

3.32.6. **KCOM**

System	OsBiz
Supported since version	V2_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{I}\sqrt{I}$
T.38 Fax	

¹⁾ No registration is used

²⁾ optional feature, needs to be booked at Gamma CLIP no Screening (known to Gamma as CLI Flexibility) is supported if the number is pre-approved by Gamma but not in call diversion scenarios.



3.32.7. <u>TalkTalk</u>

System	OsBiz
Supported since version	V2_R0.3.11
	24
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	ı
Features	
CLIP / CLIR	$\sqrt{}$
COLP	ı
DTMF (RFC 2833)	V
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	

3.32.8. *tlPicall*

System	OsBiz
Supported since version	V1_R3.2
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	ı
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-

tIPicall is available for existing installations. The profile should not be used for new installations



3.32.9. **Vodafone**



System	OSBiz
Released with version	V2R3
Capabilities&Features	
Account (DID/Client)	DID 1)
Multisite	yes ²⁾
CLIP / CLIR	yes / yes
COLP	-
DTMF (RFC2833/4733)	yes
Codecs G711/G729	yes / yes
T.38 Fax	yes

Remarks:

3.32.10. **VoiceFlex**

System	OsBiz		
Supported since version	V1_R1.1.0		
Provider			
SIP DID account √			
SIP Client account	-		
Features			
CLIP / CLIR	$\sqrt{}$		
COLP	$\sqrt{}$		
DTMF (RFC 2833)			
Codecs G.711/G.729	$\sqrt{/}$		
T.38 Fax	-		

3.32.11. **VolP Ltd i-Line**

System	OsBiz
Supported since version	V1_R3.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	-
COLP	-
DTMF (RFC 2833)	√/-
Codecs G.711/G.729	$\sqrt{I}\sqrt{I}$
T.38 Fax	-

¹⁾ No registration is used

²⁾ Multisite is supported by ITSP (numbers from different location areas are possible)



3.33.U.S.A.

3.33.1. **AT&T**

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	

3.33.2. **Broadcloud**

see Broadcloud Germany - France - Italy - UK - Australia - USA

3.33.3. CenturyLink


System	OsBiz		
Supported since version	V1_R1.1.0		
Provider			
SIP DID account	√ *1)		
SIP Client account -			
Features			
CLIP / CLIR	$\sqrt{I}\sqrt{I}$		
COLP	$\sqrt{}$		
DTMF (RFC 2833)	$\sqrt{}$		
Codecs G.711/G.729	√/-		
T.38 Fax			

^{*1)} CenturyLink will use customer specific server addresses, thus the profile needs to be completed during configuration of the system



3.33.4. **Fusion 360**

Codecs G711/G729





Remarks:


T.38 Fax

yes / yes 2)

no

<u>Please note that our tests have shown that fax transmission using the T.38 protocol with the Fusion 360 trunks was not successful. T.38 MUST be deactivated in the system.</u>

3.33.5. <u>IPfone</u>





Remarks:

¹⁾ Multisite is supported by ITSP (under the same registration, numbers from different location areas are possible)

²⁾ G729A is possible, but not recommended. G729AB is not supported

¹⁾ T.38 must be disabled in system



3.33.6. **Intermedia.net Inc**

System	OsBiz
Supported since version	V2_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	-
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	$\sqrt{}$
Codecs G.711/G.729	$\sqrt{/}$
T.38 Fax	-



3.33.7. **SoTel**

System	OsBiz		
Supported since version	V1_R1.1.0		
Provider			
SIP DID account			
SIP Client account √			
Features			
CLIP / CLIR			
COLP	-		
DTMF (RFC 2833)	V		
Codecs G.711/G.729	$\sqrt{/}$		
T.38 Fax	$\sqrt{}$		

3.33.8. Windstream

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	$\sqrt{}$
SIP Client account	$\sqrt{}$
Features	
CLIP / CLIR	$\sqrt{}$
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	\sqrt{N}
T.38 Fax	-

Note:

Only the actual Broadsoft Platform is tested and released.

Manual entries are needed for the Basic servers (Proxy-Registrar) depending on platform and region.

3.33.9. <u>XO</u>

System	OsBiz
Supported since version	V1_R1.1.0
Provider	
SIP DID account	
SIP Client account	
Features	
CLIP / CLIR	
COLP	-
DTMF (RFC 2833)	
Codecs G.711/G.729	$\sqrt{1}$
T.38 Fax	



Table of History

Version	Date	Changes
88	2020-06-02	Update for V3: Add new ITSP profiles:
89	2020-10-19	Update for V3R0.1: Add new ITSP profiles: TelemaxX – Germany VoipQ - Netherlands Update supported ITSP profiles: Sunrise – Switzerland (general update) Delete obsolete profiles: n/a
90	2021-03-01	Update for V3R1: Add new ITSP profiles: Voiceworks DE – Germany Update supported ITSP profiles: Voiceworks NL – Netherlands (new name) Delete obsolete profiles: n/a
91	2021-12-13	Update for V3R1.2: Add new ITSP profiles: KPN TLS NL – Netherlands Pocos NL - Netherlands rgi VoIP Trunk 200 – Germany Scaldis B.V Netherlands Update supported ITSP profiles: Ecotel sip Trunk 2.0 – support of Geo-Redundancy purtel – stopped T.38 Fax service



Version	Date	Changes
		Telekom Company Flex – no switch back to the primary SIP outbound proxy within 15 minutes (hidden parameter – automatically active) Telekom DLAN SIP Trunk – no switch back to the primary SIP outbound proxy within 15 minutes (hidden parameter – automatically active) Obsolete profiles (to be deleted in upcoming HotFix): KPN TLS NDL – Netherlands Pocos NDL - Netherlands
92	2022-06-01	Update for V3R2: Add new ITSP profiles:
93	2022-06-08	2 nd Update for V3R2: Released without profiles: envia TEL - Germany
94	2022-12-01	Update for V3R2.1: Add new ITSP profiles: Sparks Voice Connect – Australia Orange BE SIP – Belgium Keyyo - France EasyFone – Germany envia TEL – Germany G9 Telecom - Portugal Released without profiles: n/a Update supported ITSP profiles: Orange BE S&F - Belgium KPN TLS NL – Netherlands Vodafone Anlagenanschluss R4 – Germany Sunrise - Switzerland Delete obsolete profiles: Orcon Ltd – Australia TelstraClear WSIP - Australia



Version	Date	Changes
95	2023-10-06	Update for V3R3: Add new ITSP profiles: Drei Business SIP Connect – Austria Dstny – France Komro – Germany Magenta – Austria RoutIT TLS- Netherlands Vodafone Anlagenanschluss R5 – Germany Released without profiles: Helinet - Germany htp Business FleX Smart – Germany Update supported ITSP profiles: BT Wholesale – UK Telekom Company Flex - Germany Delete obsolete profiles: ecotel sipTrunk Connect 1.0 – Germany ecotel sipTrunk DDI – Germany Tele 2 – Austria UPC Austria – Austria Vodafone Anlagenanschluss – Germany Vodafone Anlagenanschluss R3 – Germany
96	2023-12-11	2 nd Update for V3R3: Released without profiles: BITel Business SIP Flex- Germany Gamma NGN (DE) – Germany wittenberg-net GmbH - Germany Update supported ITSP profiles: EWE Voice+ SIP Trunk Flex - Germany