

OpenStage M3 Family

Reliable, seamless connectivity in any environment





Stability, security and flexibility for your mobile personnel

Mobile workers need to be reachable at all times, as they move around the office, campus or on-site.

Cordless phones allow your on-campus workers to collaborate anywhere while on site without missing important calls or running up expensive mobile charges. Unify's OpenStage M3 is an industry-leading, multipurpose cordless phone family for use with DECT (Digital Enhanced Cordless Telecommunications) networks, specifically designed for demanding mobile employees working in tough industrial environments.

The OpenStage M3 devices give your employees the freedom to communicate effectively and safely from anywhere in the workplace and enables increased team collaboration, user productivity and flexibility. Whether industrial workers in noisy or even explosive environments, mobile security teams in high-risk scenarios or healthcare workers in emergency situations, these users require unique capabilities from their mobile device to ensure their ability to connect immediately is never compromised. With a device protection class of IP65, the OpenStage M3 DECT family handsets are designed to perform in hostile environments. These cordless phones deliver superb audio quality optimized for noisy environments and offer a wide range of variants, covering different alarm options for workplaces with security critical areas. Ergonomic and stylish with a modern, cellphone-like look, the OpenStage M3 family offers cost-effective, optimum functionality and comfortable operation with an intuitive, user-friendly interface for quick access to key communications features.

Robust, intuitive and cost-effective

Removing barriers to mobile communication, even in the most challenging situations

Which OpenStage M3 handset is right for you?

With a selection of four different models, our OpenStage M3 DECT family gives you various safety and security options designed for your employees' unique needs.

All these handsets are built to perform in harsh environments where moisture, dirt, shocks, dust or high ambient noises could compromise communication quality. Our Ex models are engineered for even tougher circumstances, such as potentially explosive atmospheres.

Our OpenStage M3 devices can operate in temperatures ranging from -10 °C to + 55 °C and they all come with a builtin alarm triggering options. Our Plus models provide maximum security with additional alarm features to connect personnel in security-critical areas where heightened supervision is needed.

OpenStage M3

The standard M3 handset is designed for tough environments and comes with basic alarm features.

OpenStage M3 Plus

Equipped with advanced alarm features including automated man down and no movement alarms, the OpenStage M₃ Plus handset is ideal for the protection of solitary workers or staff working in hazardous areas or situations.

OpenStage M3 Ex

The OpenStage M3 Ex handset offers basic alarm features and is suitable for use in harsh or potentially explosive environments.

OpenStage M3 Ex Plus

Designed for maximum protection, the OpenStage M3 Ex Plus handset comes with advanced alarm features including automated man down and no movement alarms, and is suitable for use in harsh or potentially explosive environments.

OpenStage M3 models at a glance

Key Features	OpenStage M3	OpenStage M3 Plus	OpenStage M3 Ex	OpenStage M3 Ex Plus
Alarm button with optional different behavior by long and short press	 ✓ 	\checkmark	\checkmark	\checkmark
Alarm monitoring by an LED on the front of the handset	 ✓ 	\checkmark	\checkmark	\checkmark
Up to 3 preconfigured alarm numbers	\checkmark	\checkmark	\checkmark	\checkmark
Acoustic beacon (emergency signal) at alarm location	 ✓ 	\checkmark	\checkmark	\checkmark
Automatic call with alarm	 ✓ 	\checkmark	\checkmark	\checkmark
Configurable key lock (including or excluding alarm button)	\checkmark	\checkmark	\checkmark	\checkmark
Alarm configuration protected by a Service PIN	\checkmark	\checkmark	\checkmark	\checkmark
Location information of handset with alarm	 ✓ 	\checkmark	\checkmark	\checkmark
No movement, man down, time, escape, technical, and pull cord alarm		\checkmark		\checkmark
Each alarm type can use an own alarm number		\checkmark		\checkmark
Configurable pre-alarms		\checkmark		\checkmark
Advanced alarm scenarios with or without an alarm server (like OpenScape Alarm Response)		\checkmark		\checkmark
IP65-certified housing, with protection against water and dust	 ✓ 	\checkmark	\checkmark	\checkmark
Operating temperature: -10 °C to + 55 °C (14 °F to 131 °F)	\checkmark	\checkmark	\checkmark	\checkmark
Shock-proof and break-proof	 ✓ 	\checkmark	\checkmark	\checkmark
Suitable for gas-filled environment*			\checkmark	\checkmark
Suitable for dust-filled environment**			\checkmark	\checkmark
Interference suppression in accordance with EN 6100-6-2	\checkmark	\checkmark	\checkmark	\checkmark
Acoustics optimized for industrial environments	\checkmark	\checkmark	\checkmark	 Image: A start of the start of

* Suitable for gas zone 1 explosive (Ex approval for hazardous gas: II 2G Ex ib IIC T4 Gb) ** Suitable for dust zone 21 explosive areas (Ex approval for hazardous dust: II 2D Ex tb IIIC T120°C Db) Permissible ambient temperature: -10 °C ≤ Ta ≤ +55 °C

Key benefits

- Four variants including explosive and advanced alarming
- · Modern, cell phone-like, best-in-class user interface
- Comparable feature set with desktop phones with the added benefit of mobility
- · Excellent voice quality, even in noisy environments
- Convenient operation, even in dim light
- PC interface via Bluetooth or Mini-USB
- Large private phonebook
- Integrated alarm clock and organizer functionality
- Configurable ringer and alarm tones

- Suitable for HiPath Positioning System
- Illuminated keypad and navigation area
- Illuminated 1.8" large TFT graphical display with brilliant color
- Up to 17 hours talk time and up to 200 hours standby time
- Multi-cell capability (roaming and seamless handover)
- Multi-DECT system capability (parallel registration option) with up to four DECT systems
- DECT Security (identity, authentication, encryption)
- Economic price/capability ratio



Accessories

- Selection of cases and belt clips
- Desktop chargers with country-specific power supply units
- Additional battery packs
- Headset options: wired and wireless

Connectivity and Compatible Products

The OpenStage M3 handsets can be connected to the following systems*:

- OpenScape Enterprise (for OpenScape 4000)
- HiPath Cordless Office (for HiPath 3000/ OpenScape Business)
- HiPath Cordless IP (for SIP Interfaces such as OpenScape Office/ OpenScape Voice)

Supported Software

• Gigaset QuickSync Software (PC tool) - Version 8.3 and higher

Technical Data

Range

• Up to 50 m indoors, up to 300 m outdoors

Handset

- Encryption/decryption in accordance with DECT standards
- Power supply: lithium-ion battery, 1000 mA
- Charging time: approx. 4 hours

Weight

- Handset + batteryw: approx. 166 g
- Charging unit: approx. 118 g

Color

- Handset: silver/black
- Charging unit: black

Dimensions (H × W × D in mm)

- Handset: 154 × 56 × 26
- Charging unit: 89,5 x 86 x 36



Unify is the Atos brand for communication and collaboration solutions. At the core of the Atos Digital Workplace portfolio, Unify technology enables organizations of all sizes to transform the way they collaborate, creating a more connected and productive workforce which can dramatically improve team performance, individual engagement and business efficiency.

The information provided in this document contains merely general descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract. Availability and technical specifications are subject to change without notice.

Unify, OpenScape, OpenStage and HiPath are registered trademarks of Unify Software and Solutions GmbH & Co. KG. All other company, brand, product and service names are trademarks or registered trademarks of their respective holders.



About Atos

Atos is a global leader in digital transformation with 112,000 employees and annual revenue of c. \in 11 billion. European number one in cybersecurity, cloud and high performance computing, the Group provides tailored end-toend solutions for all industries in 71 countries. A pioneer in decarbonization services and products, Atos is committed to a secure and decarbonized digital for its clients. Atos is a SE (Societas Europaea) and listed on Euronext Paris.

The purpose of Atos is to help design the future of the information space. Its expertise and services support the development of knowledge, education and research in a multicultural approach and contribute to the development of scientific and technological excellence. Across the world, the Group enables its customers and employees, and members of societies at large to live, work and develop sustainably, in a safe and secure information space.

Find out more about us atos.net atos.net/career

Let's start a discussion together



Atos is a registered trademark of Atos SE. November 2022. © Copyright 2022, Atos SE. Confidential Information owned by Atos group, to be used by the recipient only. This document, or any part of it, may not be reproduced, copied, circulated and/or distributed nor quoted without prior written approval of Atos.